



LED Eco Downlight DM6L110SP40 **93011620**

Product information

GE Lighting introduces a range of LED Eco Downlights with a selection of sizes and colour temperature options. They are finished to a high standard and are ideal for use in high-end applications such as retail, hospitality or offices.

Application areas






🛆 Retail









Product data

Dimensions	ø173×89
Limited Warranty	3 Yrs
Energy efficiency class (EEC)	A+
IP Rating	20
Certifications	CB/CE
Mounting type	Recessed
Weight [kg]	0,135
DIALux description	GE - LED Eco Downlight - 800lm - 10W - 4000K - 80CRI - 93011620[SKU] - Recessed
Body colour	White

Performance data

Rated life L70/B50 [h]	40000
Nominal life [h]	40000
Operating Voltage	120-240V
Ambient Temperature [°C]	40°C
Nominal lumens [lm]	800
Nominal correlated colour temperature (CCT) [K]	4000
Colour rendering index (CRI) [Ra]	80
Total system power	10

Electrical data

Controllability

Not dimmable electronic (Static)


Logistic data

Product status	Available
Pack quantity	1 pc./pack







Photometric Data



Technical drawing









Downloads & Links

Go to the catalog site (HTTP)

- High-resolution image (HTTP)
- LED Eco Downlight Gen2 Data Sheet (PDF)
- LED Eco Downlight Installation guide (PDF)
- LED Eco Downlight images (HTTP)
- Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)