





Albeo™ LED Luminaire -ABR1 series

ABR172H479NDSTANW1PK

93032248

# **Product information**

Albeo™ continues to build on groundbreaking high bay and low bay LED luminaires. The Albeo™ ABR1-Series expands the product offering to include an IP66 rated fixture for hightemperature (up to 65°C) industrial environments.

#### **Application areas**



(ໝ) Industrial





## **Product data**

Dimensions	406mm x 490mm x 86mm
Energy efficiency class (EEC)	A++
IP Rating	66
Certifications	CE
Impact resistance	IK08
Mounting type	Suspended
DIALux description	GE - Albeo™ LED Luminaire - ABR1 series - 22600lm - 178W - 4000K - 70CRI - 93032248[SKU] - Suspended
Dimmability	YES

## Performance data

Ambient Temperature [°C]	-30 to +60
Nominal lumens [lm]	22600
Rated life [h]	100000
Nominal correlated colour temperature (CCT) [K]	4000
Colour rendering index (CRI) [Ra]	70
Total system power	178

## **Electrical data**

Controllability	Dimmable electronic (DALI)	

## Logistic data

Product status	Available
Pack quantity	1










93032248




#### **Photometric Data**







# **Technical drawing**







# Albeo™ LED Luminaire – ABR1 series

ABR172H479NDSTANW1PK

93032248

#### **Downloads & Links**

Go to the catalog site (HTTP)

Albeo™ LED Luminaire – ABR1 series Data sheet (PDF)

Albeo™ LED Luminaire – ABR1 series Fiche Technique FR (PDF)

Albeo™ LED Luminaire – ABR1 series Images (HTTP)

All Albeo™ LED Luminaire – ABR1 series photometric files (ZIP)

**Lighting design tools & calculators (HTTP)** 

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)