



Albeo™ LED Luminaire -ABR1 series ABR174T471NDSTANW1PK 93031792

Product information


Albeo[™] continues to build on groundbreaking high bay and low bay LED luminaires. The Albeo™ ABR1-Series expands the product offering to include an IP66 rated fixture for hightemperature (up to 65°C) industrial environments.

Application areas











Product data

Dimensions	826mm x 490mm x 86mm
Energy efficiency class (EEC)	A++
IP Rating	66
Certifications	CE
Impact resistance	IK08
Mounting type	Suspended
DIALux description	GE - Albeo™ LED Luminaire – ABR1 series - 34800lm - 250W - 4000K - 70CRI - 93031792[SKU] - Suspended
Dimmability	YES

Performance data

Ambient Temperature [°C]	-30 to +65
Nominal lumens [lm]	34800
Rated life [h]	100000
Nominal correlated colour temperature (CCT) [K]	4000
Colour rendering index (CRI) [Ra]	70
Total system power	250

Electrical data

Controllability	Dimmable electronic (DALI)


Logistic data

Product status	Available
Pack quantity	1






Photometric Data



Technical drawing





[IX]



Downloads & Links

Go to the catalog site (HTTP) Albeo™ LED Luminaire – ABR1 series Data sheet (PDF) Albeo™ LED Luminaire – ABR1 series Fiche Technique FR (PDF) Albeo™ LED Luminaire – ABR1 series Images (HTTP) All Albeo™ LED Luminaire – ABR1 series photometric files (ZIP) Lighting design tools & calculators (HTTP) Certificate for the Quality Management System of GE Lighting EMEA (PDF) Certificate for the Environmental Management System of GE Lighting EMEA (PDF)