



Lumination<sup>TM</sup> LED Luminaires IS-Series IS147A2MDSLVR IHNS **93012514** 

# **Product information**


Lumination<sup>™</sup> LED Luminaires – IS Series are designed to deliver efficient lighting for commercial applications. These efficient lighting fixtures have a long life and deliver a remarkably efficient 105-110 lumens per watt allowing for lower maintenance and operating costs.

#### **Application areas**



A Retail







#### Product data

Dimensions	260×169×1256mm
Energy efficiency class (EEC)	A++
IP Rating	20
Certifications	CB/CE
Impact resistance	IK02
Mounting type	Suspended
DIALux description	GE - Lumination™ LED Luminaires IS-Series - 3880lm - 34.5W - 3500K - 80CRI - 93012514[SKU] - Suspended / Pendant
Dimmability	YES

# Performance data

Nominal lumens [lm]	3880
Nominal correlated colour temperature (CCT) [K]	3500
Colour rendering index (CRI) [Ra]	80
Total system power	34.5

#### **Electrical data**

Controllability

Dimmable electronic (DALI)

# Logistic data


Product status

Available





**Photometric Data** 



# Downloads & Links

Go to the catalog site (HTTP)

Lighting design tools & calculators (HTTP)

Lumination™ LED Luminaires – IS Series Data sheet (PDF)

Installation guide (PDF)

All images/technical drawings and photometric files (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)