



Lumination™ LED Luminaires IS-Series IS147B3MVSLVREL IHNS

93012582

Product information

Lumination™ LED Luminaires – IS Series are designed to deliver efficient lighting for commercial applications. These efficient lighting fixtures have a long life and deliver a remarkably efficient 105-110 lumens per watt allowing for lower maintenance and operating costs.

Application areas







93012582

Product data

++
`
B/CE
02
uspended
E - Lumination™ LED Luminaires IS-Series - 5045lm - 7.5W - 4000K - 80CRI - 93012582[SKU] - Suspended / endant
ES
() () E

Performance data

Nominal lumens [lm]	5045
Nominal correlated colour temperature (CCT) [K]	4000
Colour rendering index (CRI) [Ra]	80
Total system power	47.5

Electrical data

Controllability Dimmable electronic (0-10V)

Logistic data


Product status Available



Lumination™ LED Luminaires IS-Series IS147B3MVSLVREL IHNS

93012582

Photometric Data



Downloads & Links

Go to the catalog site (HTTP)

Lighting design tools & calculators (HTTP)

Lumination™ LED Luminaires – IS Series Data sheet (PDF)

Installation guide (PDF)

All images/technical drawings and photometric files (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)