ITUNGSRAM

Innovation is our heritage EST. 1896









LED Soft Strip LSS04-24-27-60 TU 93088751

Product information

GE Introduces a range of LED soft strip in a variety of lumen outputs, colour temperatures and IP ratings. This flexible LED solution can be used in a variety of applications including, hospitality, industrial, architectural and signage. The versatility of this product makes it suitable for almost any application where space may be limited.

Application areas





Hospitality



Product data

Mounting type	Surface mount
IP Rating	20
Certifications	CE
Weight [kg]	0,180
DIALux description	TUNGSRAM - LED Soft Strip - 370lm - 4.8W - 2700K - 80CRI - 93088751[SKU] - Surface mount
Dimensions	5000mm x 11mm x 3mm
Limited Warranty	3 years
Energy efficiency class (EEC)	A+

Performance data

Nominal life [h]	25000
Operating Voltage	24VDC
Ambient Temperature [°C]	25°C
Weighted energy consumption [kWh/1000h]	24.00
Rated efficacy [lm/W]	77
Lumen per Meter	370
System Wattage per Meter	4,8
Watts / Module (Strip)	24
Total system power	4.8
Nominal lumens [lm]	370
Rated power [W]	24.0
Rated Life [Hours]	25000
Nominal correlated colour temperature (CCT) [K]	2700
Colour rendering index (CRI) [Ra]	80

Optical data

Nominal beam angle [°] 120



Electrical data


Controllability Not dimmable electronic (Static)


Logistic data

Product status Available

Pack quantity 10×5 m rolls per box

Technical drawing









Downloads & Links

Go to the catalog site (HTTP)

Datasheet (PDF)

Datasheet (PDF)

Installation guide (PDF)

All images and technical drawings (HTTP)

