THORN

Diamond Edge[™]



"The Useful Light" - a unique, innovative light distribution to efficiently light your ways

- Innovative microprism optics provide the ideal balance of comfort and efficiency
- Slim profile for discreet building integration
- Efficient edge lit LEDs deliver high quality light
- Specialised light profile reduces waste light and lowers energy consumption

Applications

- Stairwells
- Corridors
- Circulation Areas
- Hallways
- Footpaths
- Landing Areas

Lamp information

- \bullet Lifetime: up to 50 000hrs @ L85 B50 Ta 25°C. For standard variants.
- 1100lm, 1900lm
- Luminaire efficacy: 85 lm/W, 76 lm/W
- Colour Temperature: 4000K
- CRI: 83



slim profile

Light Source







(€ IK10 IP65





Cross section of Diamond Edge diffuser showing high efficiency specular reflection





Overview





Ordering Guide

Description	Wt (Kg)	SAP Code
DIAMOND EDGE 1100		
DIAMOND EDGE 1100-840 HF WH	1.87	96644534
DIAMOND EDGE 1100-840 HFI WH	1.93	96644535
DIAMOND EDGE 1100-840 COR MWS WH	2.01	96644536
DIAMOND EDGE 1100-840 HF MWS WH	1.96	96644537
DIAMOND EDGE 1900		
DIAMOND EDGE 1900-840 HF WH	1.97	96644538
DIAMOND EDGE 1900-840 HFI WH	1.97	96644539
DIAMOND EDGE 1900-840 COR MWS WH	2.05	96644540
DIAMOND EDGE 1900-840 HF MWS WH	2.05	96644541

Electronic, fixed output gear HFI Electronic, DALI/DSI dimmable

MWS Microwave Sensor

WH White

Materials/Finish

Body: polycarbonate, white finish

Diffuser: clear polycarbonate with white microprism layer

Installation/Mounting

Suitable for interior or exterior wall mounting. Simple installation with central BESA fixing and rear cable entry

Specification

Slim wall mounted LED luminaire in polycarbonate with asymmetric light distribution of 1100lm or 1900lm.

As Thorn Diamond Edge.

Art Nr: 96644108



