Product Environmental Profile

Mureva Lights






General information

Representative product	Mureva Lights - IMT47214					
Description of the product	This product is an outdoor lighting, is Class I and must be Earthed.					
Functional unit	Provide lighting that delivers an outgoing artificial luminous flux of 1,000 lumens during a reference lifetime of 35,000 hours. This product is used to connect to a 230VAC 50Hz power supply. The light source of this luminaire is not replaceable. The function unit is accordance with the following technical data: - Assumption: Environmental impact of PEP (for 1,000 lumens over 35,000 hours) = Environmental impact of the reference product x (1,000 / 10,000) x (35,000 / 50,000) = Reference product environmental impact x 0.07 - Input voltage: 230V - Input current: 0.446A - Power factor: 0.9					

Constituent materials

Reference product mass

2025.5 g including the product, its packaging and additional elements and accessories



Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 8 June 2011 and EU 2015/863) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium, flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers – PBDE), or phthalates (Bis(2-ethylhexyl) phthalate - DEHP, Butyl benzyl phthalate - BBP, Dibutyl phthalate – DBP, Diisobutyl phthalate - DIBP) as mentioned in the Directive

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page

Additional environmental information


	The Mureva Lights presents the following relevent environmental aspects					
Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified					
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 115.5 g, consisting of cardboard(91%), PE bag(9%)					
Installation	Ref IMT47214 does not require any installation operations					
Use	The product does not require special maintenance operations.					
	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials This product contains electronic card (145g) that should be separated from the stream of waste so as to optimize end-of-life treatment.					
End of life	The location of these components and other recommendations are given in the End of Life Instruction document whic is available on the Schneider-Electric Green Premium website					
http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page						
	Recyclability potential: Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).					

Environmental impacts

Reference life time	10 years					
Product category	Other equipments - Active product					
Installation elements	No special installation components need during installation phase, but transport of packaging to disposal, and disposal of packaging accounted for during installation.					
Use scenario	The product is in active mode 50% of the time with a power use of 25.8W , for 10 years					
Geographical representativeness	Eourpe					
Technological representativeness	This product is an outdoor lighting, is Class I and must be Earthed.					
	Manufacturing	Installation	Use	End of life		
Energy model used	Energy model used: China	Electricity mix; AC; consumption mix, at consumer; 220V; CN	Electricity mix; AC; consumption mix, at consumer; 220V; CN	Electricity mix; AC; consumption mix, at consumer; 220V; CN		

Compulsory indicators Mureva Lights - IMT47214							
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	1.19E-04	1.18E-04	0*	0*	3.53E-07	0*
Contribution to the soil and water acidification	kg SO ₂ eq	9.41E-02	6.81E-03	8.35E-05	0*	8.72E-02	4.36E-05
Contribution to water eutrophication	kg PO ₄ ³⁻ eq	2.37E-02	6.81E-04	1.92E-05	0*	2.30E-02	1.30E-05
Contribution to global warming	kg CO ₂ eq	8.19E+01	1.42E+00	1.83E-02	0*	8.04E+01	2.70E-02
Contribution to ozone layer depletion	kg CFC11 eq	8.65E-07	2.23E-07	0*	0*	6.40E-07	1.34E-09
Contribution to photochemical oxidation	$kg C_2H_4 eq$	1.08E-02	4.38E-04	5.96E-06	0*	1.03E-02	4.40E-06
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m3	9.90E-02	9.17E-03	0*	0*	8.98E-02	2.13E-05
Total Primary Energy	MJ	1.34E+03	2.18E+01	2.59E-01	0*	1.32E+03	2.10E-01

. - - - -



Optional indicators		Mureva Ligh	ts - IMT47214				
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	1.23E+03	1.35E+01	2.57E-01	0*	1.22E+03	1.70E-01
Contribution to air pollution	m³	8.53E+03	1.78E+02	0*	0*	8.35E+03	1.49E+00
Contribution to water pollution	m³	4.15E+03	1.43E+02	3.01E+00	0*	4.00E+03	1.96E+00
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	9.14E-03	9.14E-03	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	6.84E+01	8.66E-01	0*	0*	6.75E+01	0*
Total use of non-renewable primary energy resources	MJ	1.27E+03	2.10E+01	2.58E-01	0*	1.25E+03	2.10E-01
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	6.82E+01	7.19E-01	0*	0*	6.75E+01	0*
Use of renewable primary energy resources used as raw material	MJ	1.47E-01	1.47E-01	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	1.27E+03	2.08E+01	2.58E-01	0*	1.25E+03	2.10E-01
Use of non renewable primary energy resources used as raw material	MJ	1.88E-01	1.88E-01	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	5.16E+00	2.37E+00	0*	0*	2.59E+00	2.03E-01
Non hazardous waste disposed	kg	1.69E+01	2.30E+00	0*	0*	1.46E+01	0*
Radioactive waste disposed	kg	2.15E-03	1.66E-03	4.63E-07	0*	4.81E-04	1.10E-06
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	9.18E-02	8.89E-03	0*	7.55E-03	0*	7.54E-02
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	4.43E-03	0*	0*	0*	0*	4.43E-03
Exported Energy	MJ	2.33E-05	2.19E-06	0*	2.12E-05	0*	0*

^{*} represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.8.1, database version 2016-11 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number	ENVPEP1910004_V1	Drafting rules	PCR-ed3-EN-2015 04 02
Date of issue	10/2019	Supplemented by	PSR-0014-ed1.0-EN-2018 07 18
Validity period	5 years	Information and reference documents	www.pep-ecopassport.org

Independent verification of the declaration and data

Internal X External

The elements of the present PEP cannot be compared with elements from another program.

Document in compliance with ISO 14021:2016 « Environmental labels and declarations - Self-declared environmental claims (Type II environmental labelling) »

Schneider Electric Industries SAS

Country Customer Care Center

http://www.schneider-electric.com/contact

35, rue Joseph Monier

CS 30323

F- 92506 Rueil Malmaison Cedex

RCS Nanterre 954 503 439 Capital social 896 313 776 €

www.schneider-electric.com

ENVPEP1910004_V1

Published by Schneider Electric

© 2019 - Schneider Electric – All rights reserved

10/2019