		Open space												Warehouse aisle			
	100	) lux	200 lux		300 lux				500 lux				150-200 lux				
Approx mounting height	3m	5m	3m	5m	3m	5m	7m	10m	3m	5m	7m	10m	3m	5m	7m	10-14m	
Liteline IP44 600	Х																
Liteline IP44 1200	Х	Χ	Χ		Χ												
Liteline IP44 1200 Boost		Χ	Х	Х	Χ								Χ				
Liteline IP65 1200 840	Х		Χ														
Liteline IP65 1500 840		Χ		Х	Χ	Χ											
Indline IP23 L Wide beam					Χ				Х				Х	Х			
Indline IP23 XL Wide beam						Χ			Х	Х				Х			
Indline IP23 L Medium beam						Х											
Indline IP23 XL Medium beam						Χ	Х	Χ		Х	Χ	Х			Х		
Indline IP23 L Narrow beam																Χ	
Indline IP23 XL Narrow beam																Χ	

Select the type of luminaire according to the application area. See protection class and other markings under each product.

The luminaires above are not recommended in corrosive environments. Examples of corrosive environments are cattle stalls, pig stalls, poultry stalls, car washes, lubrication pits, public bath or the like. In these environments, both luminaires and fasteners must be able to withstand corrosion.

Plastic luminaires must be intended for the environment in questions, and the plastic may need to withstand detergents and corrosive gases such as ammonia.

At Hide-a-lite, we would be pleased to help you with your lighting calculation. Get in touch and we'll tell you more!