



Peanut - IP65 fitting for LED in an unique design

Description

Industry or all-purpose design fitting with transparent diffuser. Body in transparent or opal polycarbonate. The locking of the diffuser is integrated in the diffuser and the body. Inner part with all electro technical equipment in white painted galvanized steel. MIRO quality reflector is available.

The fitting is available in 3 versions:

- ES - Essential - meets all requirement with a competitive price.
- PR - Premium - the best LED technology giving the highest light technical qualities combined with smart control systems.
- High - versions for higher ceiling heights.

LED unit	ES 1200	ES1500	PR 1200	PR 1500	High 1500
Effect:	45W	55W	56W	70W	70W
Colour temperature:	4000K	4000K	4000K	4000K	4000K
Luminous flux - lm:	4250	5350	6350	7800	8550
Luminous efficiency lm/W:	94	97	113	111	122
Colour tolerance MacAdam:	3	3	3	3	3
Life time L70:	50.000hr	50 000hr	50 000hr	50 000hr	50 000hr

Application areas

Commercial kitchen, food industry, shops, corridors, P-house and outdoor facilities.

Control gear

Electronic control gear (HF) 1-10V dimming, digital dimming DSI or DALI on request.

Mounting

Surface mounted direct in ceiling, on wall or on wire. Enclosed fixing brackets are moveable, c-c between 725 and 890 mm.

Installation

Two IP67 sealings for cable 6-13 mm is enclosed. Cable entries through 4 knock outs in top of the body. Connection through 5-pole push in terminal block, max 2,5 mm². Through wiring possibility.



Version for high ceilings with reflector (High).



Through wiring.



Fixing bracket.

Number	Type	Diffuser	Colour	Light source	Weight (kg)
117207	Peanut ES LED	1200mm	Opal	TW 45W 840 4250lm	2,5
117208	Peanut ES Detect LED	1200mm	Opal	TW 45W 840 4250lm	2,5
117219	Peanut ES LED	1500mm	Opal	TW 55W 840 5350lm	2,8
117220	Peanut ES Detect LED	1500mm	Opal	TW 55W 840 5350lm	2,8
117213	Peanut PR LED	1200mm	Opal	TW 56W 840 6350lm	2,5
117214	Peanut PR Detect LED	1200mm	Opal	TW 56W 840 6350lm	2,5
117215	Peanut PR LED	1500mm	Opal	TW 70W 840 7800lm	2,8
117216	Peanut PR Detect LED	1500mm	Opal	TW 70W 840 7800lm	2,8
117217	Peanut PR Detect LED	1200mm	Opal	TW 56W 840 6350lm	Radio MinMax 2,8
117218	Peanut PR Detect LED	1500mm	Opal	TW 70W 840 7800lm	Radio MinMax 3,1
117253	Peanut PR LED	1200mm	Opal	56W 840 6350lm	DALI 2,5
117261	Peanut PR LED	1500mm	Opal	70W 840 7800lm	DALI 2,8
117262	Peanut PR High LED	1500mm	Clear	TW 70W 840 8550lm	

Reservation for misprinting or product changes