



Futurix LED - a watertight industry fitting IP65 ideal for use in rough environments.

Description

Surface mounted industry fitting with diffuser and wide light distribution. Body in light grey glass-fibres armed polyester. Diffuser in opal/frosted polycarbonate (IK08) giving a evenly and soft and light. Fixing clips in stainless steel.

Application areas

Industry facilities, agriculture, cold-storage room, garage, parking, warehouse...

Mounting

Direct in ceiling or on wall. Available with fixing brackets to avoid taking holes in the body.

Installation

Cable entries with sealings in both ends, knock-outs on top of the fitting. Through wiring facility as standard with 5x2,5mm² push-in terminal block in each end.

LED driver

Electronic- and high-frequency LED-driver from approved manufacturers.

Others

Fittings each circuit - 16-B

17/23W		33 pcs.
17/23W	DALI	38 pcs.
30/37/56W		24 pcs.
30/37/56W	DALI	24 pcs.

LED unit (system effect)	17W	23W	30W	37W	56W	66W
Colour temperatur - K:	4000	4000	4000	4000	4000	4000
Luminous flux fitting - lm:	2210	3120	4420	5530	7760	9030
Luminous efficiency fitting - lm/W:	130	136	147	149	139	137
Coutour index Ra:	80	80	80	80	80	80
Colour tolerance MacAdam:	3	3	3	3	3	3
Expected lifetime L70B10 - t:	65.000	65.000	65.000	65.000	65.000	65.000
Ambient temperatur - Ta max:	40°C	40°C	40°C	40°C	30°C	30°C

Number	Type	Diffuser	Colour	Light source	Weight (kg)
119361	Futurix	Opal	Grå	LED 17W 840	2,0
119956	Futurix	Opal	Grå	LED 23W 840	2,3
118751	Futurix	Opal	Grå	LED 30W 840	2,9
119294	Futurix	Opal	Grå	LED 37W 840	3,8
119295	Futurix	Opal	Grå	LED 56W 840	3,8
120479	Futurix	Opal	Grå	LED 37W 840	Sensor
120582	Futurix	Opal	Grå	LED 56W 840	Sensor
121196	Futurix	Opal	Grå	LED 66W 840	
121197	Futurix	Opal	Grå	LED 66W 840	DALI