

ATEXOR code	SFN1LED....
Product description	Explosion protected luminary for fixed use
ATEX and IECEx marking	 Ex II 2 G Ex eb mb op is IIC T4 Gb Ex II 2 D Ex tb op is IIIC T90°C Db
Temperature classification	T4 (internal) T90 °C (external)
Operating temperature	-40°C ... +55°C
Light source	1 Led module with SafeEye® technology
Light emitted at source	2825 lm
Luminous flux (measured)	1595 lm
Colour temperature	4600 - 5700 K
Colour rendering index	>80
Photobiological safety	Exempt group (No marking required, safe in normal use)
Supply Voltage	230VAC/DC +/- 6%, 50/60Hz
Supply Current (typical)	230V~0,1 A
Electrical class	Class 1 (230 VAC)
Power	< 25 W
Cable	Upto 5x4mm ² . 1x M25 cable gland, ø9-17mm, delivered with blanking plug.
Enclosure	Dissipative materials (PC & TPE)
Ingress protection	IP66
Weight (without cable and fixings)	1,8 kg
Accessories	70918 extended ceiling fixing 70908 pole fixing 70908 1 pole fixing, pole above fixing

Product model	Dimensions / mm	
	L	Ø
SLAM® FIXED Novo 1LED	614	112





