Illumination material

Light chain

- With plug and end piece
- External dimensions approx. 5.30 x 13.30 mm
- Includes rubber plug and end piece with hook
- Without light bulb
- Only in combination with LED light bulb max. 1 W / 2 W P45 / 4 W A60

#	E Constantino de la c	-
740.005	10 m cable With 10 E 27 lamp holders Green	AF Y
740.006	20 m cable With 20 E 27 lamp holders Green	
		· · · · · · · · · · · · · · · · · · ·



Lamp holders

#		80	
Illumination	lamp holder E27 For outdoor use Heat and weather resistant thermoplastic	101	
740.000	Max. 40 W Protection class II/IP44 Up to 165 °C without sealing ring Splash-proof when used with sealing ring (740.001/740.012) – please order separately	740.000	740.011
Illumination lamp holder with mounting base Black For fixing to firm surfaces Only use outside with rubber seal Sealing ring (740.001/740.012) – please order separately			
740.010	E 14 Fixing screw spacing: 40 mm		
740.011	E 27 Fixing screw spacing: 46 mm		

Sealing ring for illumination lamp holders

• For fitting or retrofi tting lamp holders to light chains for outdoor use

Guaranteed drip water protection when bulb is directed downwards

#		
740.001	E 27 Black	
740.012	E 14 Black	
		740.001

Accessories for illumination light chains

#			
Connection	box	C M	
740.015	Black For flat cables H05RN H2-F, 5.0 x 13.0 mm	740.015	740.004
End piece for	or illumination cable	740.015	740.004
740.004	Black DIN 0282 With hook for hanging For securing the cable end	-	
Flat couplin	g for illumination cable	The second	6-10
740.003	Black DIN 0282 With hinged lid and mounting Without earthing contact For contour plugs only		
Flat cable p	lug for illumination cable 16 A/250 V~	740.003	740.002
740.002	Black DIN 49406 For cables H05RN H2-F2x 1.5 mm ² , solid rubber version Without earthing contact With snap latch	412	
Solid rubbe	right-angled plug		
740.017	Black IP44 For flat cable With snap latch With screw terminals Assembled with two screws from front		

740.017

