

Helena Park – decorative fitting in a Nordic design

## Description

Housing and base are made of die-cast aluminium and top cover in hot galvanized steel. The rods are of aluminium and the diffuser of clear or opal PMMA acrylic. The fitting is delivered in grey, RAL 7035 as standard.. The reflector shield is made of aluminium, painted in white. Changeable LED module available as accessory for re-building of existing fittings.

## Application areas

Footpaths, entrances, parks, pedestrian streets, parking area etc...

## Mounting

The fitting is prepared for mounting on Ø60 pole top or on a wall bracket.

## Installation


Supplied with 4m 3x1,5mm<sup>2</sup> cable.

## Installation

Ellipsiod light source with frosted finish is recommended.


## Others

Also available as Wall and Bollard fitting.



OUTDOOR

Number	Type	Diffuser	Colour	Light source	Weight (kg)
103623	Helena Park	Clear	Grey	TC-TEL 1x57W GX24q-5 HF	8,3
101815	Helena Park	Clear	Grey	HSE/HIE 1x70/50W-E E27	8,3
115787	Helena Park	Opal	Grey	HSE/HIE 1x70/50W-E E27	8,3
Accessory:					
101274	Wall arm bracket		Stainless steel		



Reservation for misprinting or product changes