



Scoop – plain and solid fitting for smaller streets, pedestrian areas and sport tracks

## Description

The housing is made of die-cast aluminium, painted in grey. The locking clips and surface screws are all made of stainless steel. Aluminium reflector. Curved glass in a hardened quality. Compensated as standard supplied with cut-off ignitor. IP65 class I. Delivered without light source.

## Application areas

Scoop is a good quality/value fitting in aluminium and is ideal for use in floodlit tracks, pedestrian roads, parking areas and rural application areas.

## nMounting/Installation

Scoop is delivered with a reversible fixing bracket adapted for pole tops and arms Ø42, 48 and 60 mm. Terminal block 3x4mm<sup>2</sup> with possibility for manual disconnection without use of tooling. Cable Ø 1-13mm. Membrane grommet IP65 safe guard the protection class even when using 3 separate cables. The fitting can be opened from top without any tooling.

Wind surface 0,09m<sup>2</sup>



Horizontal and vertical bracket for pole and arm Ø42 - 48 - 60mm.



Lamp change and service from top of the fitting.

STREET - TUNNEL

Nummer	Type	Colour	Light source	Weight(kg)
3533041	Scoop	Grey	HST/HIT 70/50W E27	6,5

*Delivered with reversible bracket for pole top and arm Ø42-48-60mm included*