

Helena Park – decorative fitting in a Nordic design

## Description

Housing and base are made of die-cast aluminium and top cover in hot galvanized steel. The rods are of aluminium and the diffuser of clear or opal PMMA acrylic. The fitting is delivered in grey, RAL 7035 as standard.. The reflector shield is made of aluminium, painted in white. The LED module is changeable and available as accessory for re-building of existing fittings.

## Application areas

Footpaths, entrances, parks, pedestrian streets, parking area etc...

## Mounting


The fitting is prepared for mounting on Ø60 pole top or on a wall bracket.

## Installation

Supplied with 4m 3x1,5mm<sup>2</sup> cable.

## Others

Also available as Bollard fitting.



OUTDOOR

## LED module

	Clear	Clear	Opal	Opal
Effect from fitting:	45W	45W	45W	45W
Colour temperature:	3000K	4000K	3000K	4000K
Luminous flux LED module:	3900 lm	4300 lm	3900 lm	4300 lm
Luminous flux fitting:	1943 lm	2144 lm	2586 lm	2854 lm
Luminous efficiency fitting:	43 lm/W	47,5 lm/W	57,5 lm/W	63,5 lm/W
Colour index Ra:	85			
Colour tolerance MacAdam:	3 SDCM			
Expected life time L70:	90 000 h			
Ambient temperatur Ta:	25°C			

Number	Type	Diffuser	Colour	Light source	Weight (kg)
115740	Helena Park	Clear	Grey	LED 840 40W	7,6
115741	Helena Park	Opal	Grey	LED 840 40W	7,6
115742	Helena Park	Clear	Grey	LED 830 40W	7,6
115743	Helena Park	Opal	Grey	LED 830 40W	7,6
Accessory:					
101274	Wall arm bracket		Stainless steel		