

Sensor-switched LED floodlight

# XLED slim S

white

EAN 4007841 012069

Article number 012069



LED

30 years (Ø 4,5h / day)

3000 K

3000K warm-white



infrared sensor  
160°



max. 8 m



IP44



2 - 1000 lux



2 sec - 70 min



Light source not  
exchangeable



Control gear not  
exchangeable



ideal 2 m

## Function description

Light meets elegance. Elegantly designed sensor LED floodlight XLED slim S with 7,2 W, ideal for building entrances and pathways, pleasant and effective light (720 lm) requiring very little energy, sensor reach of up to 8 m.

## Technical specifications

Dimensions (L x W x H)	201 x 66 x 241 mm
With lamp	Yes, STEINEL LED system
With motion detector	Yes
Manufacturer's Warranty	3 years
Settings via	Potentiometers
Version	white
PU1, EAN	4007841012069
Application, place	Outdoors
Application, room	outdoors, all round the building, terrace / balcony
Colour	white
Includes corner wall mount	No
Installation site	wall
Installation	Wall, Surface wiring
Impact resistance	IK03
IP-rating	IP44
Protection class	I
Ambient temperature	-20 – 40 °C

Mechanical scalability	No
Reach, radial	r = 4 m (22 m²)
Reach, tangential	r = 8 m (89 m²)
Photo-cell controller	Yes
Cover material	sticker
Luminous flux total product	720 lm
Measured luminous flux (360°)	720 lm
Total product efficiency	100 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM3
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Service life LED L70B50 (25°)	> 60000 h
Drop in luminous flux in accordance with LM80	L70B10
LED cooling system	Active and Passive Thermo Control
Soft light start	No

<https://www.steinel.de>

Subject to technical modifications

01.2023 Page 1 from 3

Sensor-switched LED floodlight

# XLED slim S

white

EAN 4007841 012069

Article number 012069



## Technical specifications

Housing material	Aluminium	Time setting	2 s – 70 Min.
Cover material	Plastic, transparent	Main light adjustable	No
Mains power supply	220 – 240 V / 50 – 60 Hz	Interconnection	No
Mounting height max.	4,00 m	Output	7,2 W
Sneak-by guard	Yes	Colour Rendering Index CRI	= 82
Electronic scalability	No	Optimum mounting height	2,2 m
		Detection angle	160 °

Sensor-switched LED floodlight

# XLED slim S


white

EAN 4007841 012069

Article number 012069



## Detection Zone




Mögliche Montagehöhe: 1,80 m – 4,00 m

Orange: radial

Schwarz: tangential

## Dimension Drawing



## Circuit diagram

