

Sensor-switched LED floodlight

# Spot Way SC

with motion detector & Bluetooth

EAN 4007841 058661

Article number 058661



LED

20.000 h

3000 K

3000K warm-white



38°



infrared sensor 90°



max. 10 m



Twilight switch



IP44



Light source not  
exchangeable



Control gear not  
exchangeable



2 - 1000 lux

## Function description

Timeless look. Quickly interconnected. The elegant, swivelling ground spotlight (57 cm) with 90° infrared sensor stylishly and brightly sets off driveways, garden parts etc. with 512 lm of warm-white light at 3000 K. Convenient interconnection, adjustment and control via free app. This makes child's play of selecting time and twilight settings, ON/OFF times as well as grouping lights. Includes mains plug (2.5 m) and lamp.

## Technical specifications

Dimensions (L x W x H)	226 x 140 x 572 mm
With lamp	Yes, LED lamp
With motion detector	Yes
Manufacturer's Warranty	3 years
Settings via	Bluetooth
Version	with motion detector & Bluetooth
PU1, EAN	4007841058661
Application, place	Outdoors
Application, room	outdoors, garden
Colour	Anthracite
Includes corner wall mount	No
Installation site	Stand mounted
Installation	Stand mounted
Impact resistance	IK03
IP-rating	IP44
Protection class	I
Ambient temperature	-20 – 40 °C

Mechanical scalability	No
Reach, radial	r = 2 m (3 m <sup>2</sup> )
Reach, tangential	r = 10 m (79 m <sup>2</sup> )
Photo-cell controller	Yes
Luminous flux total product	512 lm
Measured luminous flux (360°)	512 lm
Total product efficiency	64,8 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM5
Lamp	LED can be replaced
Soft light start	No
Continuous light	selectable, 4h
Functions	Manual ON / ON-OFF, Timer, Master/slave override
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Basic light level function	No

<https://www.steinel.de>

Subject to technical modifications

01.2023 Page 1 from 2

# Spot Way SC


with motion detector & Bluetooth  
 EAN 4007841 058661  
 Article number 058661

## Technical specifications

Housing material	Aluminium
Cover material	Plastic, transparent
Mains power supply	220 – 240 V / 50 – 60 Hz
Slave mode selectable	Yes
Sneak-by guard	No
Capability of masking out individual segments	No
Electronic scalability	No

Main light adjustable	No
Twilight setting TEACH	Yes
Interconnection	Yes
Interconnection via	Bluetooth
Output	7,9 W
Colour Rendering Index CRI	= 81
Detection angle	90 °

## Detection Zone



Mögliche Montagehöhe: –  
 Orange: radial  
 Schwarz: tangential

## Dimension Drawing

