#### Outdoor light without sensor

## L 835 C

without motion detector, with Bluetooth EAN 4007841 079260 Article number 079260











IP44



2 - 2000 Lux















Energie sparen

**Function description** 

State-of-the-art light cubes. The cubic L 835 C LED outdoor light without sensor sets every external home wall perfectly in scene with its elegant look and warm white LED light (3,000 K) and 616 lm. Ideal for terraces, home entrances and facades. Several lights can be interconnected to form light groups via app. If a sensor-controlled light is included, all lights switch ON automatically as soon as movement is detected. Colour: Anthracite.

## **Technical specifications**

Dimensions (L x W x H)	110 x 110 x 110 mm		
Dimensions (Ø x H)	132 x 110 mm		
With lamp	Yes, STEINEL LED system		
Manufacturer's Warranty	3 years		
Settings via	Connect Bluetooth Mesh, Smartphone, Tablet		
With remote control	No		
Version	without motion detector, with Bluetooth		
PU1, EAN	4007841079260		
Application, place	Outdoors		
Application, room	outdoors, garden, front door, courtyard & driveway, all round the building, terrace / balcony		
Colour	Anthracite		
includes sheet of self-adhesive numbers	No		
Installation site	wall		
Impact resistance	IK03		

Output	9,1 W	
Photo-cell controller	No	
Luminous flux total product	616 lm	
Measured luminos flux (360°)	616 lm	
Total product efficiency	68 lm/W	
Colour temperature	3000 K	
Lamp	LED cannot be replaced	
LED life expectancy (max. °C)	50000 h	
Service life LED L70B50 (25°)	> 60000 h	
Base	without	
LED cooling system	Passive Thermo Control	
Soft light start	No	
Continuous light	selectable	
Basic light level function	No	
Main light adjustable	0 - 100 %	
Twilight setting TEACH	No	
Interconnection	Yes	

## Outdoor light without sensor

# L 835 C

without motion detector, with Bluetooth EAN 4007841 079260 Article number 079260



## **Technical specifications**

IP-rating	IP44	
Protection class	II	
Ambient temperature	-20 - 40 °C	
Housing material	Plastic	
Cover material	Plastic, opal	
Mains power supply	220 – 240 V / 50 – 60 Hz	

Interconnection via	Bluetooth Mesh Connect
Colour Rendering Index CRI	= 82

## **Dimension Drawing**

## **Light Distribution Curve**

Output	9,1 W
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
Measured luminos flux (360°)	616 lm
Colour temperature	3000 K
Colour Rendering Index	80-89
LED life expectancy (max. °C)	50000 h
LED cooling system	Passive Thermo Control