



SLC Shadow 2xSchuko 2x5W 3CCT TED IP65/54

24/10/2023

SLC1410



Product description

Introducing SLC Shadow, the perfect outdoor ceiling lamp to light up your outdoor space with style and functionality. With its sleek and minimalistic design, 2 x schuko sockets, adjustable beam angle and changeable CCT, SLC Shadow will enhance any outdoor setting.

SLC Shadow features a unique wall wash effect that spreads light upwards and downwards, creating a beautiful ambience. The beam angle is individually adjustable, from 15 to 120 degrees, so you can customize the lighting to suit your needs.

LC Shadow also comes with two Schuko sockets, allowing you to easily plug in electrical appliances like a lawn mower, speaker, camera, or any other device you might need in your outdoor space.

Crafted with the highest quality materials and designed to withstand the harshest weather conditions, Shadow is built to last. So whether you want to enhance your backyard, patio, or outdoor living area, SLC Shadow is perfect. Illuminate your outdoor space in style with SLC Shadow.



Technical data

Suitable for wall mounting	Yes
Lamp type	LED not exchangeable
Surface protection housing	Powder coating
Material cover	Plastic, transparent
Nominal voltage	220 - 240 Volt
Light distributor	Focal lens
Beam angle	Variable beam angle
Light outlet	Direct
Degree of protection (IP)	IP54
Rated ambient temperature according to IEC	-20 - 40 Degrees celsius

Suitable for surface mounting	Yes
Housing material	Aluminium
Housing colour	Black
Voltage type	AC
Dimming phase cut-off	Yes
Light sharing	Symmetric
Colour consistency (McAdam ellipse)	SDCM3
Rated life time L70/B50 at 25 °C	50000 Hour
Protection class	I
Max. system power	10 Watt





Luminaire efficacy	65 Lumen/Watt
Colour of light	White
Colour rendering index CRI	80-89
Width	130 Millimetre
Length	165 Millimetre
Conductor cross section	2,5 Square millimetre
Photobiological safety according to EN 6247	RG1
Luminous flux adjustable	Positions
GTIN	7070938070904
RAL Colour	RAL9005

Rated luminous flux according to IEC 62722-	650 Lumen
Colour temperature	2700 - 4000 Kelvin
Power factor	90
Height/depth	125 Millimetre
Number of poles	3
Connection type	Screw terminal
Colour of light adjustable	Positions
Beam angle adjustable	Continuously variable
Produced by	The Light Group

