

BORG0 PRISON

Wall-mounting fitting
with switch for correctional
environments.



BVCert. 6037554



Borgo Prison



Mini-Borgo Prison

Features:




- Very compact cell wall fitting
- Rip-out resistant
- > 65° inclined top
- Vandal-resistant switch
- Body in ZP 10/10 steel
- Frame in ZP 20/10 steel
- Polyester powder-coated finish
- Clear pebble polycarbonate diffuser
- Opal polycarbonate diffuser
- CCT 4000 K, CRI min. 80
- Stainless steel vandal-resistant screws

☐ RAL9003


Options available on request:

- 3000 K LEDs
- Switch on left



 Vandal-resistant tool (bit) to be ordered separately
code: 9800 0004



L : 390
Borgo Prison



L : 200
Mini-Borgo Prison



BORG0 LED IP65 with switch

 **direct 532**

220-240 V AC / 50/60 Hz   RoHS				
Length (mm)	Power (W)	Luminaire light output (lm)	Luminaire efficacy (lm/W)	Code switch on right
390	8	725	91	5324 1400
	17	1700	100	5325 1400

Lumen maintenance: L80B10 / over 72,000 hours

Lumen maintenance: L90B50 / 52,000 hours

Fluorescent version: contact us

BORG0 LED IP20 with switch and socket

 **direct 532**

220-240 V AC / 50/60 Hz   RoHS				
Length (mm)	Power (W)	Luminaire light output (lm)	Luminaire efficacy (lm/W)	Code switch on right
390	8	725	91	5326 1400
	17	1700	100	5327 1400

Lumen maintenance: L80B10 / over 72,000 hours

Lumen maintenance: L90B50 / 52,000 hours

Fluorescent version: contact us

Additional options Borgo

Coding:

add the corresponding suffix to the product code: e.g. **5324 1400** ----

 **9413** flat Duroflam® diffuser

9415 flat opal PC diffuser

MINI-BORG0 PRISON LED with switch

 **direct 534**

220-240 V AC / 50/60 Hz   RoHS			
Power (W)	Luminaire light output (lm)	Luminaire efficacy (lm/W)	Code switch on right
11	925	84	5340 0400

Lumen maintenance: L80B10 / over 72,000 hours

Lumen maintenance: L90B50 / 52,000 hours