

## GUELL ZERO A/W



|                                           |                                     |
|-------------------------------------------|-------------------------------------|
| <b>Part number</b>                        | 06148680                            |
| <b>Lampholder:</b>                        | LED                                 |
| <b>Light Source:</b>                      | LED                                 |
| <b>Wattage:</b>                           | 15 W                                |
| <b>Finish:</b>                            | BK-RAL9005 / Black RAL9005 / Glossy |
| <b>Insulation class:</b>                  | I                                   |
| <b>Degree of protection:</b>              | IP66                                |
| <b>IK-J-xxIP:</b>                         | IK06 1.2J xx3                       |
| <b>CRI:</b>                               | 80                                  |
| <b>Kelvin:</b>                            | 4000                                |
| <b>Power factor:</b>                      | $\text{COS}\phi \geq 0,9$           |
| <b>Optic:</b>                             | Asymmetric Wide Reflector           |
| <b>Lightsource lumen output:</b>          | 1888 lm                             |
| <b>Luminaire lumen output:</b>            | 1472 lm                             |
| <b>L:</b>                                 | L70                                 |
| <b>B:</b>                                 | B10                                 |
| <b>Lifetime:</b>                          | 150000 h                            |
| <b>Ta MIN luminaire:</b>                  | -15°                                |
| <b>Ta MAX luminaire:</b>                  | 35°                                 |
| <b>ULR:</b>                               | 0%                                  |
| <b>IPEA* (Street Lighting):</b>           | A++                                 |
| <b>IPEA* (Area Lighting):</b>             | A3+                                 |
| <b>IPEA* (Cycle/Pedestrian Lighting):</b> | A++                                 |
| <b>IPEA* (Green Areas):</b>               | A++                                 |
| <b>IPEA* (Historical Areas):</b>          | A5+                                 |
| <b>Luminous Intensity Class:</b>          | G*6                                 |




### Description


LED floodlight for indoor and outdoor lighting, comprising:

- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
- Flat tempered glass diffuser
- Diffuser permanently sealed to the housing through a high temperature resistant silicone glue
- Very high performance asymmetrical reflector made of 99.99% plated aluminium, polished, oxidised and free of iridescence
- Stainless steel external screws
- Stainless steel locking springs for the glass
- Powder coated steel bracket
- Complete with 1 metre of cable H05RN-F 3G1 mm<sup>2</sup>
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings



## OPTIONAL ACCESSORIES

### GUELL ZERO



14453380  
500 mm arm completes with  
connection base GUELL ZERO

Black RAL9005



14453480  
1000 mm arm completes with  
connection base GUELL ZERO

Black RAL9005