

GUELL ZERO A/W



Part number	06148585
Lampholder:	LED
Light Source:	LED
Wattage:	15 W
Finish:	WH-RAL9010 / White RAL9010 / Glossy
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK06 1.2J xx3
CRI:	80
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	Asymmetric Wide Reflector
Lightsource lumen output:	1888 lm
Luminaire lumen output:	1472 lm
L:	L70
B:	B10
Lifetime:	150000 h
Ta MIN luminaire:	-15°
Ta MAX luminaire:	35°
ULR:	0%
IPEA* (Street Lighting):	A++
IPEA* (Area Lighting):	A3+
IPEA* (Cycle/Pedestrian Lighting):	A++
IPEA* (Green Areas):	A++
IPEA* (Historical Areas):	A5+
Luminous Intensity Class:	G*6




Description


LED floodlight for indoor and outdoor lighting, comprising:

- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
- Flat tempered glass diffuser
- Diffuser permanently sealed to the housing through a high temperature resistant silicone glue
- Very high performance asymmetrical reflector made of 99.99% plated aluminium, polished, oxidised and free of iridescence
- Stainless steel external screws
- Stainless steel locking springs for the glass
- Powder coated steel bracket
- Complete with 1 metre of cable H05RN-F 3G1 mm²
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings



OPTIONAL ACCESSORIES

GUELL ZERO



14463585
500 mm arm completes with
connection base GUELL ZERO

White RAL9010



14463485
1000 mm arm completes with
connection base GUELL ZERO

White RAL9010