

## GUELL 2 S/W



|                                           |                                  |
|-------------------------------------------|----------------------------------|
| <b>Part number</b>                        | 06094294                         |
| <b>Lampholder:</b>                        | LED                              |
| <b>Light Source:</b>                      | LED                              |
| <b>Wattage:</b>                           | 78 W                             |
| <b>Finish:</b>                            | GR-94 / Metallic grey / Textured |
| <b>Insulation class:</b>                  | I                                |
| <b>Degree of protection:</b>              | IP66                             |
| <b>IK-J-xxIP:</b>                         | IK07 3J xx5                      |
| <b>CRI:</b>                               | 80                               |
| <b>Kelvin:</b>                            | 4000                             |
| <b>Power factor:</b>                      | $\cos\phi \geq 0,9$              |
| <b>Optic:</b>                             | SYMMETRIC WIDE REFLECTOR         |
| <b>Lightsource lumen output:</b>          | 11116 lm                         |
| <b>Luminaire lumen output:</b>            | 9520 lm                          |
| <b>L:</b>                                 | L70                              |
| <b>B:</b>                                 | B10                              |
| <b>Lifetime:</b>                          | 150000 h                         |
| <b>Ta MIN luminaire:</b>                  | -20°                             |
| <b>Ta MAX luminaire:</b>                  | 30°                              |
| <b>ULR:</b>                               | 0%                               |
| <b>IPEA* (Street Lighting):</b>           | A6+                              |
| <b>IPEA* (Area Lighting):</b>             | A7+                              |
| <b>IPEA* (Cycle/Pedestrian Lighting):</b> | A4+                              |
| <b>IPEA* (Green Areas):</b>               | A4+                              |
| <b>IPEA* (Historical Areas):</b>          | A10+                             |
| <b>Luminous Intensity Class:</b>          | G*6                              |




### Description


LED floodlight for indoor and outdoor lighting, comprising:

- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
- Flat tempered glass diffuser
- Very high performance symmetrical reflector made of 99.99% plated aluminium, polished, oxidised and free of iridescence
- Anti-ageing silicone gasket
- Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
- Stainless steel external screws
- Fully integrated stainless steel aluminium spring clips
- Powder coated steel bracket
- Versions with dimmable ballast available. Consult Factory
- Consult factory for other colour temperatures and colour rendering index
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data




### Technical drawings



## OPTIONAL ACCESSORIES

### GUELL 2



14173502  
Protective grid GUELL 2



14174220  
Connection box IP 66



14173394  
Wall support 500 mm/19.69" GUELL  
1/2  
  
Metallic grey




14173494  
Wall support 1000 mm/39.37" GUELL  
1/2  
  
Metallic grey



14174094  
Single pole top support GUELL 2  
  
Metallic grey




14174194  
Double pole top support GUELL 2  
  
Metallic grey



14460594  
Reinforcing bracket GUELL 2 in  
painted steel. Used to fasten the  
floodlight with a single screw in the  
centre of the bracket  
  
Metallic grey

### GUELL 2 S/W



14173720  
Louvre GUELL 2 Symmetrical