## ENOLA SQUARE UP/-DOWN S

## outdoor LED surface-mounted wall light anthracite

The ENOLA SQUARE and ROUND series of puristic luminaires consist of a cylindrical or square aluminium construction, and are equipped with powerful LEDs. The light colour can be switched between 3000K and 4000K during installation using the built-in CCT. Because of the built-in LED driver, the electrical connection of the luminaire is made directly to a 230V mains voltage supply. In order to cover as wide a range of uses as possible, single and double headed wall lights and ceiling lights are available in round and square version in various sizes. This luminaire contains built-in LED lamps.

## **TECHNICAL DATA**

\_

Item no.	1003418
Number of different light outlets	2
IP Code	IP 65
Impact resistance class	IK 06
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall,Wall with Acc.
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	10
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	1
Wattage	7.8 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	12.4 A
Duration of inrush current	7.2 µs
Stroboscopic effect (SVM)	0.03
Lumen	620 / 700 lm
Colour temperature	3000/4000 Kelvin
Beam angle	30 °

## Light Source

916542	
Accessories	
1002853	Spacer set , for outdoor wall-mounted lights an- thracite
1005262	ENOLA S , chrome re- flector 60°

Color	anthracite
CRI	90
LXXBXX data	L70B50
Service life	30000 h
Risk Group	1
Width	7 cm
Height	18 cm
Depth	11.5 cm
Net weight	1.08 kg
Gross weight	1.26 kg
BIG WHITE Page	616