




IMPERVA 120 CW

LED Outdoor wall and ceiling light, IP66, grey, 4000K

The functional wall and ceiling light has a diffuser which creates a pleasant light distribution. The luminaire was designed with powerful LEDs and is available in several lengths. The IP luminaire can be fitted with a warm white or cool white LEDS as required. Thanks to the built-in ballast, the luminaire is ready for direct connection to the 230V mains voltage supply.



TECHNICAL DATA

Item no.	1001315
IP Code	IP 66
Impact resistance class	IK 08
Assembly	Surface
Assembly details	Ceiling, Wall
Number of through-wires	45
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	40 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Stroboscopic effect (SVM)	0.02
Lumen	5095 lm
Colour temperature	4000 Kelvin
Beam angle	120 °
Color	grey
CRI	80
LXXBXX data	L70B50
Service life	50000 h
Risk Group	1
Length	116 cm

Light Source

916325		Width	12 cm
		Height	10.8 cm
		Net weight	2.297 kg
		Gross weight	2.583 kg
		BIG WHITE Page	692