





DASAR 215

outdoor inground fitting, TC-(D,H,T,Q)SE, IP67, round, stainless steel 316, max. 80W

The high-voltage DASAR 215 UNI inground light is accessible and impresses with its stainless steel screen and glass cover in a partial satin finish. With its IP 67 protection class, it is optimally suited for outdoor use. Thanks to the rotatable and pivoting E27 fitting, direct the light cone individually. The housing is made of high-quality 316 stainless steel and glass. When will you test out the benefits of SLV's impressive outdoor lights?



TECHNICAL DATA

Item no.	229200
Socket	E27
Number of sockets	1
IP Code	IP 67
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground
Mechanical loading	2 t
Primary nominal voltage	220-240V ~50/60Hz
Safety class	I
Wattage	11 W
Color	stainless steel
Light distribution	symmetric
Light outlet	direct
Depth	22.5 cm
Diameter	21.5 cm
Net weight	3.397 kg
Gross weight	4.222 kg
Shape of cut-out	round
Installation depth	28.3 cm
Installation diameter	20 cm

Recommended lamp

1005298	LED light , QPAR111 GU-10 12W 680lm 3000K CRI90 55° dimmable
1005299	LED light , QPAR111 GU-10 12W 750lm 4000K CRI90 55° dimmable