




## DASAR 80

outdoor inground fitting, QPAR51, IP67, square, stainless steel 316, max. 35W

The high-voltage inground light DASAR 80 QPAR51 inground light is accessible and impresses with its stainless steel screen and glass cover in a partial satin finish. Thanks to the rotatable and pivoting GU10 fitting, you can direct the light cone flexibly. And thanks to its IP 67 protection class, it is optimally suited for outdoor areas. Then there is the high-quality housing made of 316 stainless steel and glass. When will you test out the benefits of SLV's impressive outdoor lights?



## TECHNICAL DATA

Item no.	229324
Number of sockets	1
Tilt range	30 °
Horizontal rotation range	90 °
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 67
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground
Mechanical loading	2 t
Primary nominal voltage	220-240V ~50/60Hz
Safety class	I
Wattage	35 W
Temperature at glass (light emission)	110 °C
Color	stainless steel
Light outlet	direct
Length	13 cm
Width	13 cm
Depth	16 cm
Net weight	1.111 kg
Gross weight	1.352 kg

Shape of cut-out	round
Installation depth	16.5 cm
Installation diameter	11.5 cm
BIG WHITE Page	721

## Recommended lamp

1005075	LED lightbulb QPAR51 , GU10, 2700K, grey
1005078	LED lightbulb QPAR51 , GU10, 3000K, grey
1005081	LED lightbulb QPAR51 , GU10, 4000K, grey
1005273	QPAR51 GU10 , LED light, 6W 2200 2700K CRI90 36°