TERANG 2

outdoor wall and ceiling light, LED, 3000K, IP44, oval, white, max. 11W

A new interpretation of the classical construction luminaires for wall and ceiling mounting with a pre-installed powerful LED module. Available with housing colours of white, silver-grey, anthracite and rust, the TERANG 2 XL has frosted round glass, which guarantees homogeneous distribution of its light. With protection class IP44, this luminaire is also designed for use outdoors. Thanks to its pre-installed LED driver, the TERANG 2 is ready for direct connection to a 230V mains supply.





TECHNICAL DATA

Item no.	229931
IP Code	IP 44
Impact resistance class	IK 03
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling,Wall
Primary nominal voltage	220-240V ~50/60Hz
Safety class	I
Wattage	11 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Stroboscopic effect (SVM)	3.6
Lumen	830 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	20000 h
Width	19.8 cm
Height	11 cm
Depth	7.5 cm

Light Source

954795	

Net weight	0.457 kg
Gross weight	0.557 kg
BIG WHITE Page	692