




H-POL

pathway and floor stand, double-headed, LED, 3000K, anthracite, L/W/H 16.5/16.5/66 cm

The H-POL DOUBLE indirect radiating floor stand is made of aluminium and plastic. With protection class IP55, it is suitable for outdoor use. Thanks to the two 8W LEDs, the luminaire is ideal for use as a pathway light. The product is designed for floor installation and is through-wireable. A large mounting pot is available for optimum mounting in the earth. Thanks to the built-in LED driver, it can be connected directly to the 230V mains supply.



TECHNICAL DATA

Item no.	232185
Number of different light outlets	2
IP Code	IP 65
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Assembly	Recessed
Assembly details	Ground, Ground with Acc.
Number of through-wires	9
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	1000 mA
Safety class	I
Wattage	35 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	10 A
Duration of inrush current	300 µs
Stroboscopic effect (SVM)	0.01
Lumen	1400 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	anthracite
CRI	80

Light Source

916393	
--------	---

Accessories

232195	MOUNTING POT , for H-POL pathway and floor stand, anthracite
--------	--

LXXBXX data	L70B50
Service life	30000 h
Risk Group	0
Length	16.5 cm
Width	16.5 cm
Height	66 cm
Net weight	2.547 kg
Gross weight	3.34 kg
Shape of cut-out	square
Installation length	11.8 cm
Installation width	11.8 cm
Installation depth	10 cm
BIG WHITE Page	573