




VILUA UP/DOWN WL

Outdoor recessed wall light, anthracite, IP54 100°

The VILUA wall light, which is equipped with powerful, warm white LEDs, is available in several versions. The two oppositely arranged light sources create two similar light beams (UP/DOWN). The electrical connection of the luminaire, which is made from aluminium, is made directly to the 230V mains supply. Thanks to its IP54 protection class, the luminaire is suitable for outdoor use. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	1002505
IP Code	IP 54
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Primary nominal voltage	100-277V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	16 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Level of inrush current	17 A
Duration of inrush current	35 µs
Stroboscopic effect (SVM)	0.01
Lumen	800 lm
Colour temperature	3000 Kelvin
Beam angle	100 °
Color	anthracite
CRI	80
LXXBXX data	L70B50
Service life	30000 h

Light Source

916530		Width	12 cm
		Height	24 cm
		Depth	6.6 cm
		Net weight	1.17 kg
		Gross weight	1.37 kg
		BIG WHITE Page	643