



100
kWh/1000h

D
energy class

18
lumens/watt

Halogen Linear

OT K12 C100W 240V R7S 78MM GE
BX1/10MIC

63525

Product information

C class Double Ended Linear

- Increased efficiency – C energy class
- More than 30% energy saving
- Retrofit to standard Double Ended Linear
- Full range 100-330W to replace 150-500W standard range

Application areas



Hospitality



Home

Product data

Product Code	63525
Bulb Shape	Tubular
Bulb Diameter [mm]	10
Maximum Overall Length [mm]	78
Net weight per piece [g]	6
Gross weight per piece [g]	9
Brand	GE Lighting
Cap/Base	R7s

Performance data

Rated Lumens [lm]	1800
Weighted energy consumption [kWh/1000h]	100.0
Energy efficiency class (EEC)	D
Lamp Lumen Maintenance factor (2000 hours)	80%
Rated Life [h]	2000
Nominal correlated colour temperature (CCT) [K]	2800
Nominal lumens [lm]	1800

Electrical data

Rated power [W]	100.0
Starting time (sec)	0.0 s
Warm up time up to 60% of full light output	instant
Number of switching cycles	8000
Dimming Capability	Yes
Nominal power [W]	100.0
Nominal lamp voltage [V]	240

Logistic data

DUN Code	10043168635254
EAN Code	0043168765305
Pack Quantity	10
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	4800 EUR, 6000 UK
Layer quantity EUR	4800
Layer quantity UK	6000
Pallet quantity EUR (PC)	24000
Pallet quantity UK (PC)	30000
Outer case size	191 x 188 x 212 (mm)
Product status	Available

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Halogen Lamps Spectrum Catalogue \(PDF\)](#)

[Halogen DEQ and IR™ DEQ Lamps Data sheet \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[Halogen Lamps Spectrum Catalogue \(PDF\)](#)

[Halogen DEQ and IR™ DEQ Lamps Data sheet \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

[Certificate for the Quality Management System of GE Lighting EMEA \(PDF\)](#)

[Certificate for the Environmental Management System of GE Lighting EMEA \(PDF\)](#)