
TUNGSRAM

Innovation is our heritage EST. 1896







GE Bright Stik™ LED 7/STIK/830/100-240/E14/F 1/15 93047729

Product information

LED Bright Stik™ illuminates spaces with light instantly. Its sleek cylindrical shape fits in place of a traditional incandescent bulb - and some sockets where a traditional bulb or CFL doesn't fit . Replace a 40W, 60W & 100W incandescent with an LED Bright Stik and keep saving for the next 15 years*. That's a long time you can spend not worrying about light bulbs.



GE Bright Stik™ LED 7/STIK/830/100-240/E14/F 1/15 93047729

Product data

Product Code	93047729
Bulb Shape	Stik
Bulb Finish	White
Bulb Diameter [mm]	32
Nominal Length [mm]	103
Net weight per piece [g]	32
Dimmability	No
RoHS compliant	Yes
Brand	GE Lighting
Cap/Base	E14

Performance data

Nominal/ Rated Beam Angle [°]	240
Rated Lumens [lm]	550
Weighted energy consumption [kWh/1000h]	7.0
Rated efficacy [lm/W]	78.5
Energy efficiency class (EEC)	A+
Rated life L70/B50 [h]	10000
Nominal correlated colour temperature (CCT) [K]] 3000	
Nominal lumens [lm]	550
Colour Rendering Index (CRI) [Ra]	80



GE Bright Stik™ LED 7/STIK/830/100-240/E14/F 1/15 93047729

Electrical data

Nominal lamp power factor	>0.5
Rated power [W]	7.0
Operating Temperature (MIN) [°C]	-20°C
Operating Temperature (MAX) [°C]	+40°C
Starting time (sec)	< 0.5 s
Number of switching cycles	100000
Dimming Capability	No
Nominal lamp voltage range [V]	100-240
Nominal power [W]	7.0

Logistic data

DUN Code	10064894557559
EAN Code	0064894557552
Pack Quantity	15
Inner pack type	Box
Outer pack type	Carton
Product status	Available

Downloads & Links

Go to the catalog site (HTTP)

Product datasheet (PDF)

User Manual for the Bright Stik™ products (PDF)

Images (HTTP)

Lighting design tools & calculators (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

