

Innovation is our heritage EST. 1896





LED T8 Value Glass

LEDT8 VG 1.8m 24W 830 100-240V 1/10 TU

93116715

Product information

The LED T8 VG Glass range offers safe, reliable and affordable energy saving alternatives to standard Fluorescent T8 lamps. Available in 60cm, 120cm, 150cm and 180cm lengths, GE LED T8s can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear or on electronic gear with a simple re-wire (for further details see installation guide).



LED T8 Value Glass LEDT8 VG 1.8m 24W 830 100-240V 1/10 TU 93116715

Product data

| Product Code | 93116715 |
|------------------------------------|--------------|
| Bulb Shape | Tubular |
| Bulb Diameter [mm] | 28 |
| Regulatory comment | CE certified |
| Bulb maximum overall diameter [mm] | 28 |
| Maximum Overall Length [mm] | 1778 |
| Net weight per piece [g] | 350 |
| Mercury Content [mg] | No |
| Dimmability | No |
| UV radiance | No |
| Brand | Tungsram |
| Cap/Base | G13 |

Performance data

| Nominal/ Rated Beam Angle [°] | 200° |
|--|----------|
| Colour Code | 830 |
| Colour consistency | <6 steps |
| Lumen at 25°C [lm] | 3000 |
| Rated efficacy [lm/W] | 125 |
| Energy efficiency class (EEC) | A++ |
| Rated life L70/B50 [h] | 50000 |
| Nominal correlated colour temperature (CCT) [K]] | 3000 |
| Nominal lumens [lm] | 3000 |
| Colour Rendering Index (CRI) [Ra] | 80 |
| | |



LED T8 Value Glass LEDT8 VG 1.8m 24W 830 100-240V 1/10 TU 93116715

Electrical data

| Operating Temperature [°C] | -20+40°C |
|----------------------------------|----------|
| Operating Temperature (MIN) [°C] | -20°C |
| Operating Temperature (MAX) [°C] | +40°C |
| Design Ambient Temperature [°C] | -20+40°C |
| Startup time [sec] | <0.5 |
| Number of switching cycles | 50000 |
| Dimming Capability | No |
| Nominal lamp voltage range [V] | 100-240 |
| Nominal power [W] | 24 |

Logistic data

| Shipment | Standard |
|-----------------|----------------|
| DUN Code | 15994100056703 |
| EAN Code | 5994100056706 |
| Pack Quantity | 10 |
| Inner pack type | sleeve |
| Outer pack type | OUTER BOX |
| Layer quantity | 30 |
| Product status | Available |
| | |

Downloads & Links

Go to the catalog site (HTTP)
Installation guide (PDF)
Images (HTTP)
Datasheet (FR) (PDF)