



40
kWh/1000h

E
energy class

PAR 64

EXG PAR64/1000W/240V/WFL

93106670

Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- Choice of beam widths
- Excellent colour rendering
- High efficiency combined with low operating costs
- Robust and reliable
- UV control
- Easy retrofit
- Colour consistent throughout life
- Colour blends with halogen and fluorescent

Application areas



Club and Disco



Product data

Product Code	93106670
Light Center Length [mm]	80
Bulb Shape	PAR
Bulb Diameter [mm]	204
Maximum Overall Length [mm]	150
Net weight per piece [g]	982
Gross weight per piece [g]	1072
Brand	Tungsram
Cap/Base	GX16d

Performance data

Nominal/ Rated Beam Angle [°]	30
Nominal center beam candlepower (CBCP) [cd]	38000
Weighted energy consumption [kWh/1000h]	40.0
Energy efficiency class (EEC)	E
Rated Life [h]	300
Nominal correlated colour temperature (CCT) [K]	3200
Colour Rendering Index (CRI) [Ra]	100

Electrical data

Coil type	C-13
Dimming Capability	Yes
Ballast Required	No
Nominal power [W]	1000
Nominal lamp voltage [V]	240

Logistic data

DUN Code	15994100021411
EAN Code	5994100021414
Pack Quantity	6
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	24 EUR, 30 UK
Layer quantity EUR	24
Layer quantity UK	30
Pallet quantity EUR (PC)	120
Pallet quantity UK (PC)	150
Outer case size	536 x 391 x 196 (mm)
Product status	Available

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Entertainment Solution Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[Entertainment Pocket brochure \(PDF\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

[Certificate for the Quality Management System of GE Lighting EMEA \(PDF\)](#)

[Certificate for the Environmental Management System of GE Lighting EMEA \(PDF\)](#)

Disclaimer

Special purpose lamp – Stage Studio. Not suitable for household illumination.