

Halogeenilamput

Precise™ MR16 -lamput

Teho W	Jännite V	Kanta	Nimike	Keila ast	Valovoima cd	Keskim. polttotika h	Pakkaus- koko	Tuote- numero	SSTL
-----------	--------------	-------	--------	--------------	-----------------	-------------------------	------------------	------------------	------

ILCOS: HRGI ZWEI: QR-CBC51

Precise™ ConstantColor™ IR- suljettu, 50 mm, UV-suodatus

20	12	GU5.3	Q20MR16HIR/CCG10	10	6000	5000	20	77900	47 897 86
20	12	GU5.3	Q20MR16HIR/CCG24	24	2300	5000	20	77901	47 897 87
20	12	GU5.3	Q20MR16HIR/CCG36	36	1000	5000	20	77902	47 897 88
35	12	GU5.3	Q35MR16HIR/CCG10	10	12000	5000	20	77904	47 897 89
35	12	GU5.3	Q35MR16HIR/CCG24	24	4200	5000	20	77905	47 897 90
35	12	GU5.3	Q35MR16HIR/CCG36	36	2000	5000	20	77906	47 897 91
45	12	GU5.3	Q45MR16HIR/CCG10	10	14000	5000	20	77907	47 897 92
45	12	GU5.3	Q45MR16HIR/CCG24	24	5200	5000	20	77908	47 897 93
45	12	GU5.3	Q45MR16HIR/CCG36	36	2300	5000	20	77909	47 897 94

Precise™ ConstantColor™ - suljettu, 50 mm, UV-suodatus

20	12	GU5.3	ESX/CG	12	3150	5000	10	20858	47 894 73
20	12	GU5.3	BAB/CG	40	475	5000	10	20857	47 894 76
35	12	GU5.3	FRB/CG	12	7500	5000	10	20864	47 895 30
35	12	GU5.3	FRA/CG	20	3200	5000	10	20860	47 895 27
35	12	GU5.3	FMW/CG	40	900	5000	10	20859	47 895 24
50	12	GU5.3	EXT/CG	14	8400	6000	10	20872	47 894 79
50	12	GU5.3	EXZ/CG	25	2900	6000	10	20871	47 894 82
50	12	GU5.3	EXN/CG	40	1500	6000	10	20867	47 894 85
50	12	GU5.3	FNV/CG	55	850	6000	10	20865	47 895 33
71	12	GU5.3	EYF/CG	15	10400	4000	10	20876	47 894 88
71	12	GU5.3	EYJ/CG	25	4550	4000	10	20874	47 894 91
71	12	GU5.3	EYC/CG	40	2000	4000	10	20873	47 894 94

MR16- IR Energy Saver - suljettu, 50 mm, UV-suodatus

20	12	GU5.3	MR16 IR 20W 12V WFL	36	1000	5000	10	77657	47 897 95
35	12	GU5.3	MR16 IR 35W 12V WFL	36	2000	5000	10	77658	47 897 96

Precise™ Bright - avoin, 50 mm, UV-suodatus

20	12	GU5.3	M69/BAB	36	500	5000	10	88231	47 894 13
35	12	GU5.3	M70/FRA	18	3660	5000	10	88228	47 894 16
35	12	GU5.3	M81/FMW	36	1620	5000	10	88229	47 894 19
50	12	GU5.3	M58/EXN	36	2600	5000	10	88234	47 894 28
50	12	GU5.3	M80/FNV	60	1190	5000	10	88232	47 894 31



Precise™ MR16 -lamput

Teho W	Jännite V	Kanta	Nimike	Keila ast	Valovoima cd	Keskim. polttoikä h	Pakkaus-koko	Tuote-numero	SSTL
Precise™ Bright - suljettu, 50 mm, UV-suodatus									
20	12	GU5.3	M268/ESX/C	8	4000	5000	10	88226	47 894 38
20	12	GU5.3	M269/BAB/C	36	450	5000	10	88235	47 894 40
35	12	GU5.3	M270/FRA/C	18	2950	5000	10	88230	47 894 43
35	12	GU5.3	M281/FMW/C	36	1300	5000	10	88236	47 894 46
50	12	GU5.3	M249/EXT/C	8	8000	5000	10	88227	47 894 49
50	12	GU5.3	M250/EXZ/C	24	4750	5000	10	88237	47 894 52
50	12	GU5.3	M258/EXN/C	36	2100	5000	10	88239	47 894 55
50	12	GU5.3	M280/FNV/C	60	950	5000	10	88238	47 894 58



ILCOS: HRGI ZWEI: QR-CBC51

Precise™ Alutech - suljettu, 50mm, alumiiniheijastin, UV-suodatus

20	12	GU5.3	M269/BAB/CG/AL	36	450	3000	10	88216	47 894 61
35	12	GU5.3	M281/FMW/CG/AL	36	1300	3000	10	88217	47 894 64
50	12	GU5.3	M258/EXN/CG/AL	36	1800	3000	10	88215	47 894 67
50	12	GU5.3	M280/FNV/CG/AL	60	700	3000	10	88214	47 894 70



Precise™ MR11 -lamput

ILCOS: HRGI ZWEI: QR-CBC35

Precise™ MR11 - avoin, 35 mm

20	12	GU4	FTD/M62	26	550	3500	10	19626	47 895 12
35	12	GU4	FTF/M66	21	2300	3500	10	19635	47 895 18
35	12	GU4	FTH/M199	26	1300	3500	10	19634	47 895 21



Precise™ MR11 - suljettu, 35 mm

12	12	GU4	FTA/M264/C	8	3960	2000	10	19639	47 895 36
20	12	GU4	FTC/M251/C	17	1800	3500	10	19636	47 895 42
20	12	GU4	FTD/M262/C	26	490	3500	10	19625	47 895 45
35	12	GU4	FTF/M266/C	21	2070	3500	10	19627	47 895 51



Halogeenilamput

AR111 alumiiniheijastinhalogeeni



Teho W	Jännite V	Kanta	Nimike	Keila ast	Valovoima cd	Keskim. polttoikä h	Pakkaus-koko	Tuote-numero	SSTL
ILCOS: HMG111		ZWEI: QR111							
AR111 alumiiniheijastinhalogeeni, 12V, kanta G53									
35	12	G53	AR111 35 SP 12V	8	14000	2000	10	10774	47 891 30
35	12	G53	AR111 35 FL 12V	24	2500	2000	10	10775	47 891 32
50	12	G53	AR111 50 SP 12V	8	17800	3000	10	10766	47 891 50
50	12	G53	AR111 50 FL 12V	24	3500	3000	10	10767	47 891 52
75	12	G53	AR111 75 SP 12V	8	23500	3000	10	10768	47 891 70
75	12	G53	AR111 75 FL 12V	24	5300	3000	10	10769	47 891 72
75	12	G53	AR111 75 WFL 12V	45	1700	3000	10	10771	47 891 73
100	12	G53	AR111 100 SP 12V	8	40000	3000	10	41915	47 891 90
100	12	G53	AR111 100 FL 12V	24	8000	3000	10	41922	47 891 92
100	12	G53	AR111 100 WFL 12V	45	2300	3000	10	41923	47 891 93

CeriTite™ UV-suodatus, pienjännitehalogeenipolttimot



Teho W	Jännite V	Kanta	Nimike	Hehku-lanka	Pituus mm	Valovirta lm	Keskim. polttoikä h	Pakkaus-koko	Tuote-numero	SSTL
ILCOS: HSG/C			ZWEI: QT							
10	6	G4	M29/ESA	H	33	200	100	20	34720	47 893 37
10	6	G4	M42	H	33	140	1500	20	34728	47 893 29
20	6	G4	M34/FHE	H	33	350	2000	20	34719	47 893 41
20	6	G4	M30/ESB	H	33	450	100	20	34718	47 893 42
5	12	G4	M9	H	33	60	2000	20	42959	47 893 26
10	12	G4	M11	H	33	140	2000	20	34674	47 893 35
20	12	G4	M47	H	33	380	2000	20	34715	47 893 44
20	12	GY6.35	M76	A	44	300	4000	20	34712	47 893 47
35	12	GY6.35	M75	A	44	600	4000	20	34710	47 893 86
35	12	GY6.35	M95	H	44	550	3000	20	34708	47 893 89
50	12	GY6.35	M74	A	44	900	4000	20	34703	47 893 74
50	12	GY6.35	M32	H	44	850	4000	20	34702	47 893 71
50	24	GY6.35	M89	H	44	750	2000	20	34684	47 893 80
75	12	GY6.35	M73	A	44	1350	4000	20	34683	47 893 92
75	12	GY6.35	M313	H	44	1350	4000	20	34682	47 893 93



CeriTite™ pienjännitehalogeenipolttimot

Teho W	Jännite V	Kanta	Nimike	Hehku-lanka	Pituus mm	Valovirta lm	Keskim. polttoikä h	Pakkaus-koko	Tuote-numero	SSTL
ILCOS: HSG/C			ZWEI: QT							
100	12	GY6.35	M180	A	44	2150	4000	20	34664	47 894 04
100	12	GY6.35	M28/EVA	H	44	2200	3000	20	34676	47 893 95
100	24	GY6.35	M67	H	44	2000	2000	20	34663	47 893 98
250	24	GY6.35	M33	H	44	8400	300	100	34768	47 894 01
250	24	GY6.35	M36	H	44	5750	2000	100	29231	47 893 83



CeriTite™ UV-suodatus, pienjännitehalogeenipolttimot, pienpaine

10	12	G4	M11 CL/UV/LP	A	33	140	2000	20	35705	47 893 50
20	12	G4	M47 CL/UV/LP	A	33	320	2000	20	35710	47 893 53
20	12	GY6.35	M76 CL/UV/LP	A	44	300	2000	20	35696	47 893 56
35	12	GY6.35	M75 CL/UV/LP	A	44	600	2000	20	35699	47 893 59
50	12	GY6.35	M74 CL/UV/LP	A	44	950	2000	20	35700	47 893 62
75	12	GY6.35	M73 CL/UV/LP	A	44	1350	2000	20	35701	47 893 65

H - vaakahelkylanka

A - aksiaalinen helkylanka

Kaksikantaiset halogeenilamput

Teho W	Jännite V	Kanta	Nimike	Pituus mm	Valovirta lm	Keskim. polttoikä h	Pakkaus-koko	Tuote-numero	SSTL
ILCOS: HDG			ZWEI: QT-DE						
Kirkas, energiaa säästävä HIR -halogeeni									
375	240	R7s	K1-Q375T3/240/HIR	117	9000	2000	10	31612	47 892 81
Kirkas									
100	240	R7s	K12 C100W R7s	78	1900	1000	10	76530	47 897 62
130	240	R7s	K11 C130W R7s	117	2440	1000	10	76529	47 897 63
200	240	R7s	K9 C200W R7s	117	4000	1000	10	76528	47 897 64
330	240	R7s	K1 C330W R7s	117	7000	1000	10	76527	47 897 65
1000	240	R7s	K4	189	21000	2000	10	29181	47 892 84
1000	240	R7s	K10	254	21000	2000	6	43712	47 892 85
1500	240	R7s	K5	254	32000	1000	10	29187	47 892 87



ILCOS: HDG			ZWEI: QT-DE							
Kirkas 120V										
150	120	R7s	K12	78	2600	2000	10/100	91747		
150	120	R7s	K28	117	2100	2000	10/100	91748		
200	120	R7s	K11	117	3100	2000	10/100	91749		
300	120	R7s	K9	117	5100	2000	10/100	91750		
500	120	R7s	K1	117	9800	2000	10/100	29161		



Halogeenilamput

MR16 Mains

Teho W	Jännite V	Kanta	Nimike	Keila ast	Pituus/dia mm	Valovoima cd	Keskim. polttotika h	Pakkaus- koko	Tuote- numero	SSTL
-----------	--------------	-------	--------	--------------	------------------	-----------------	-------------------------	------------------	------------------	------

ILCOS: HAG

ZWEI: QPAR16

MR16 Mains Tech halogeenikohdelamppu, 240V, alumiiniheijastin, kanta GU10

50	240	GU10	Q50MR16 25°	25	55/51	950	3000	50	40404	47 890 50
50	240	GU10	Q50MR16 36°	36	55/51	600	3000	50	40405	47 890 52

MR16 Mains Start, halogeenikohdelamppu, 240V, alumiiniheijastin, kanta GU10

20	240	GU10	Q20MR16 38 AST	38	55/51	200	1500	50	10859	47 890 54
35	240	GU10	Q35MR16 38 AST	38	55/51	400	1500	50	10857	47 890 55
50	240	GU10	Q50MR16 38 AST	38	55/51	600	1500	50	92730	47 890 53

MR16 Mains Start, värillinen halogeenikohdelamppu, 240V, kanta GU10

50	240	GU10	Q50MR16/FL/Blue	36	55/51	Sininen	1500	50	12995	47 890 64
50	240	GU10	Q50MR16/FL/Red	36	55/51	Punainen	1500	50	12988	47 890 65
50	240	GU10	Q50MR16/FL/Yellow	36	55/51	Keltainen	1500	50	13003	47 890 66

PAR 16 halogeenikohdelamppu, kanta E14

ILCOS: HAG

ZWEI: QPAR16

40	240	E14	Q40PAR16	25	79/50	950	2000	10	27845	47 893 94
----	-----	-----	----------	----	-------	-----	------	----	-------	-----------

PAR 20 halogeenikohdelamppu, kanta E27

ILCOS: HAG

ZWEI: QPAR20

50	240	E27	50PAR20/240/SP	10	90,5/65	3000	2100	15	40364	47 893 05
50	240	E27	50PAR20/240/FL	30	90,5/65	1000	2100	15	40365	47 893 08

PAR 25 halogeenikohdelamppu, kanta E27

ILCOS: HAG

ZWEI: QPAR25

75	240	E27	Q75PAR25 FL	25	108/81	1300	2500	15	92165	47 895 73
----	-----	-----	-------------	----	--------	------	------	----	-------	-----------

PAR 30 halogeenikohdelamppu, kanta E27

ILCOS: HAG

ZWEI: QPAR30

75	240	E27	75PAR30/240/SP	10	90,5/97	6900	2000	15	40367	47 874 90
75	240	E27	75PAR30/240/FL	30	90,5/97	2200	2000	15	40361	47 874 92
100	240	E27	100PAR30/240/FL	30	90,5/97	3500	2500	15	32482	47 874 96



Halo T

Teho W	Jännite V	Kanta	Nimike	Pituus/dia mm	Valovoima lm	Keskim. polttoikä h	Pakkaus- koko	Tuote- numero	SSTL
Halo T, valonheitinhalogeeni - kanta E40									
1000	240	E40	HALOT38/1000W/E40/240	280/38	21000	2000	10	32109	47 892 99



Yksikantaiset halogeenilamput, verkkojännite

ILCOS: HSG

ZWEI: QT

G9 kanta, 240V

25	240	G9	Q25/CL/G9 240V kirkas	43/13	260	1500	10	88941	47 895 80
40	240	G9	Q40/CL/G9 240V kirkas	43/13	490	2000	10	22498	47 896 02
60	240	G9	Q60/CL/G9 240V kirkas	43/13	820	2000	10	22508	47 896 06



G9 kantaiset Energy Saver halogeenilamput

G9 kanta, 240V

18	240	G9	Q18/CL/G9 240V kirkas	43/13	170	2000	10	77086	47 897 83
28	240	G9	Q28/CL/G9 240V kirkas	43/13	340	2000	10	77085	47 897 84
42	240	G9	Q42/CL/G9 240V kirkas	43/13	630	2000	10	77084	47 897 85




Yksikantaiset halogeenilamput

GY9.5 kanta

ILCOS: HSG

ZWEI: QT

300	240/250	GY9.5	M38	80/28.5	5000	2000	24	88442	47 894 07
500	240/250	GY9.5	M40	80/30	8500	2000	24	88468	47 894 10



Hehkulampun näköiset halogeenilampput 240V

Teho W	Jännite V	Kanta	Nimike	Dia mm	Valovirta lm	Keskim. polttotika h	Pakkaus- koko	Tuote- numero	SSTL
-----------	--------------	-------	--------	-----------	-----------------	----------------------------	------------------	------------------	------

Energy Efficient HaloVakiolamppu

E27 kanta, 240V



28	240	E27	28HaloA/CL/E27	50	340	2000	8	76954	47 897 66
42	240	E27	42HaloA/CL/E27	50	630	2000	8	76950	47 897 67
70	240	E27	70HaloA/CL/E27	50	1300	2000	8	76945	47 897 68
100	240	E27	100HaloA/CL/E27	50	1800	2000	8	76941	47 897 69

Energy Efficient HaloKynttilälamppu

E14 kanta, 240V



18	240	E14	18HaloC/CL/E14	36	170	2000	12	76937	47 897 70
28	240	E14	28HaloC/CL/E14	36	340	2000	12	76930	47 897 71
42	240	E14	42HaloC/CL/E14	36	630	2000	12	76569	47 897 72

Energy Efficient HaloMainos ja -koristelamppu

E14/E27 kanta, 240V



18	240	E14	18HaloS/CL/E14	45	170	2000	12	76562	47 897 73
28	240	E14	28HaloS/CL/E14	45	340	2000	12	76555	47 897 74
42	240	E14	42HaloS/CL/E14	45	630	2000	12	76548	47 897 75
18	230	E27	18HaloS/CL/E27 230V	45	170	2000	12	76565	47 897 76
28	240	E27	28HaloS/CL/E27	45	340	2000	12	76554	47 897 77
42	240	E27	42HaloS/CL/E27	45	630	2000	12	76547	47 897 78

Energy Efficient HaloReflector, heijastinlamppu

E14/E27 kanta, 240V



28	240	E14	28W Halo R50 E14	R50		2000	8	76544	47 897 79
42	240	E27	42W Halo R63 E27	R63		2000	6	76541	47 897 80
42	240	E27	42W Halo R80 E27	R80		2000	6	76538	47 897 81
70	230	E27	70W Halo R80 E27 230V	R80		2000	10	76537	47 897 82