TUNGSRAM[™]

Innovation is our heritage EST. 1896



Product information


Housing in a clear quartz bulb, these halogen floodlighting lamps have a ceramic one-pin cap on each end and can be operated on 230V or 240V mains. Linear halogen lamps provide a powerful light source for compact fittings used for floodlighting, architectural lighting and security. GE's linear halogen lamps are double ended, using the universal

R7s cap format, and are available in the two industry standards of 118mm or 78mm, plus longer, higher wattage versions.

Application areas







Product data

Product Code	93112532
Bulb Shape	Tubular
Bulb Diameter [mm]	10
Maximum Overall Length [mm]	255.5
Net weight per piece [g]	20
Gross weight per piece [g]	40
Brand	Tungsram
Cap/Base	R7s

Performance data

Rated Lumens [lm]	1740
Weighted energy consumption [kWh/1000h]	106.0
Rated efficacy [lm/W]	21.33333
Energy efficiency class (EEC)	D
Lamp Lumen Maintenance factor (2000 hours)	80%
Rated Life [h]	2000
Nominal correlated colour temperature (CCT) [K]]	3000
Nominal lumens [lm]	32000
Colour Rendering Index (CRI) [Ra]	100

Electrical data

Rated power [W]	100.0
Starting time (sec)	0.0 s
Warm up time up to 60% of full light output	instant
Number of switching cycles	8000
Coil type	C-8
Dimming Capability	Yes
Nominal power [W]	1500
Nominal lamp voltage [V]	240

Logistic data

Shipment	Standard
DUN Code	15994100030796
EAN Code	5994100030799
Pack Quantity	10
Layer quantity	180 EUR, 240 UK
Layer quantity EUR	180
Layer quantity UK	240
Pallet quantity EUR (PC)	2520
Pallet quantity UK (PC)	4080
Outer case size	381 x 124 x 60 (mm)
Product status	Available

Downloads & Links

Go to the catalog site (HTTP) Halogen Lamps Spectrum Catalogue (PDF) Halogen DEQ and IR™ DEQ Lamps Data sheet (PDF) Lighting design tools & calculators (HTTP) Lighting design tools & calculators (HTTP) High-res images / Technical drawings (HTTP) Certificate for the Quality Management System of GE Lighting EMEA (PDF) Certificate for the Environmental Management System of GE Lighting EMEA (PDF)



Tungsram is a registered trademark of Tungsram Operations Kft.

tungsram.com

We in Tungsram Operations Kft. are constantly developing and improving our products. For this reason, all product descriptions in this catalogue are intended as a general guide, and we may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this publication present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, Tungsram cannot accept any liability arising from the reliance on such data to the extent permitted by law.