



1019

kWh/1000h

C

energy class

21

lumens/watt

Halogen Tubular

HALOT38/1000W/ES/240V MIH

32109

Product information

Housing in a clear outer soft glass bulb, these halogen floodlighting lamps operated on 230V or 240V mains have an E40 cap and can be fitted directly into traditional incandescent lamp sockets. The outer bulbs contain Mains Voltage Double Ended Halogen Linear Lamps in clear bulb.

Application areas



Hospitality



Home

Product data

Product Code	32109
Bulb Shape	Tubular
Bulb Diameter [mm]	38
Maximum Overall Length [mm]	280
Net weight per piece [g]	315
Gross weight per piece [g]	350
Brand	GE Lighting
Cap/Base	E40

Performance data

Weighted energy consumption [kWh/1000h]	1018.43
Rated efficacy [lm/W]	21
Energy efficiency class (EEC)	C
Lamp Lumen Maintenance factor (2000 hours)	80%
Rated Life [h]	2000
Nominal correlated colour temperature (CCT) [K]	3000
Nominal lumens [lm]	21000
Colour Rendering Index (CRI) [Ra]	100

Electrical data

Rated power [W]	1000.0
Starting time (sec)	0.0 s
Warm up time up to 60% of full light output	instant
Number of switching cycles	8000
Coil type	C-8
Dimming Capability	Yes
Nominal power [W]	1000.0
Nominal lamp voltage [V]	240

Logistic data

DUN Code	19004102321092
EAN Code	9004102321095
Pack Quantity	10
Layer quantity	140 EUR
Layer quantity EUR	140
Pallet quantity EUR (PC)	1540
Pallet quantity UK (PC)	2000
Outer case size	295 x 210 x 100 (mm)
Product status	Available

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Halogen Lamps Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[Halogen Lamps Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

[Certificate for the Quality Management System of GE Lighting EMEA \(PDF\)](#)

[Certificate for the Environmental Management System of GE Lighting EMEA \(PDF\)](#)