

44  
kWh/1000h

A  
energy class

69  
lumens/watt

## ConstantColor™ CMH PAR 30

CMH35/PAR30/UVC/U/830/E27/SP TU  
93104653

### Product information

#### ConstantColor™ CMH lamps combine the HPS

**technology** (providing stability, efficiency & uniformity) and the Metal Halide Technology (bright white quality light) to produce highly efficient light sources with good colour rendering and consistent colour performance through life. This is achieved by using the ceramic arc tube material from the Lucalox™ lamp, which minimises the chemical changes inside the lamp through life. When combined with the halide doses used in Arcstream™

**Metal Halide lamps** then the quality and stability of the dose maintains the colour consistency. Hence the name ConstantColor™ CMH.

Metal halide lamps, traditionally made with quartz arc tubes, are prone to colour shift through life and lamp-to-lamp colour variation. Some of the dose, e.g. sodium, (an important component of metal halide lamps), can migrate through quartz to cause colour shift and loss of light through life. The ceramic arc tube resists this material loss, can be manufactured to tighter tolerances and

withstands a higher temperature to  
provide a more constant colour.

---

## Application areas



Road and tunnel



Street and  
pedestrian



Commercial  
areas

Product data

Product Code	93104653
Bulb Shape	PAR
Bulb Finish	Clear
Bulb Diameter [mm]	95.5
Maximum Overall Length [mm]	124
Net weight per piece [g]	211
Gross weight per piece [g]	262
Operating position	U - Universal
Mercury Content [mg]	5.05
UV radiance	Exempt
Brand	Tungsräm
Cap/Base	E27

## Performance data

Nominal/ Rated Beam Angle [°]	10
Nominal/ Rated Beam Angle (°)	9.9
Colour Code	830
Nominal center beam candlepower (CBCP) [cd]	39600
Rated peak intensity in [Cd]	39600
Rated Lumens [lm]	2449
Weighted energy consumption [kWh/1000h]	43.46
Useful lumens (at 90° cone) [lm]	2449
Nominal efficacy [LpW]	69
Rated efficacy [LpW]	62
Energy efficiency class (EEC)	A
Rated average life [h]	10000
Nominal chromaticity coordinate X	0.431
Nominal chromaticity coordinate Y	0.406
Nominal correlated colour temperature (CCT) [K]	3000
Nominal lumens [lm]	2400
Colour Rendering Index (CRI) [Ra]	81


## Electrical data

Rated power [W]	39.5
Lamp Current [A]	0.5
Design Ambient Temperature [°C]	25
Run-up time (sec)	180
Dimming Capability	No
Ballast Required	Yes
Nominal power [W]	35
Nominal lamp voltage [V]	90


## Logistic data

DUN Code	15994100019197
EAN Code	5994100019190
Pack Quantity	6
Inner pack type	BOX
Layer quantity	96 EUR, 120 UK
Layer quantity EUR	96
Layer quantity UK	120
Pallet quantity EUR (PC)	672
Pallet quantity UK (PC)	840
Outer case size	278 x 188 x 143 (mm)
Product status	Available


## Light distribution



Lumen maintenance data



Survival data



## Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Photometry \(IES\)](#)

[Product datasheet \(PDF\)](#)

[High-res images / Technical drawings \(HTTP\)](#)



Tungram is a registered trademark of  
Tungram Operations Kft.

[tungram.com](http://tungram.com)

We in Tungram Operations Kft. are constantly developing and improving our products. For this reason, all product descriptions in this catalogue are intended as a general guide, and we may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this publication present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, Tungram cannot accept any liability arising from the reliance on such data to the extent permitted by law.