

T5 LongLast HE loistelamppu



Teho W	Pituus mm	Nimike	Väriämpö- tila K	Keskim polttoika h	Valovirta lm 25°C	Pakkaus- koko	Tuote- numero	SSTL
ILCOS: FDH			ZWEI: T5		Värintoistoluokka 1B	Kanta G5		
14	549	F14T5/827	2700	30.000	1227	30	90230	49 824 27
14	549	F14T5/830	3000	30.000	1227	30	90239	49 824 30
14	549	F14T5/835	3500	30.000	1227	30	90246	49 824 35
14	549	F14T5/840	4000	30.000	1227	30	90247	49 824 40
14	549	F14T5/865	6500	30.000	1227	30	90244	49 824 65
21	849	F21T5/827	2700	30.000	1909	30	90245	49 825 27
21	849	F21T5/830	3000	30.000	1909	30	90248	49 825 30
21	849	F21T5/835	3500	30.000	1909	30	90249	49 825 35
21	849	F21T5/840	4000	30.000	1909	30	90250	49 825 40
21	849	F21T5/865	6500	30.000	1909	30	90251	49 825 65
28	1149	F28T5/827	2700	30.000	2636	30	90252	49 826 27
28	1149	F28T5/830	3000	30.000	2636	30	90253	49 826 30
28	1149	F28T5/835	3500	30.000	2636	30	90254	49 826 35
28	1149	F28T5/840	4000	30.000	2636	30	90255	49 826 40
28	1149	F28T5/865	6500	30.000	2636	30	90256	49 826 65
35	1449	F35T5/827	2700	30.000	3318	30	90257	49 827 27
35	1449	F35T5/830	3000	30.000	3318	30	90258	49 827 30
35	1449	F35T5/835	3500	30.000	3318	30	90259	49 827 35
35	1449	F35T5/840	4000	30.000	3318	30	90260	49 827 40
35	1449	F35T5/865	6500	30.000	3318	30	90261	49 827 65

A

B

C

D

E

F

G

H

I

J

K



T5 LongLast HO loistelamppu

Teho W	Pituus mm	Nimike	Värlämpö- tila K	Keskim polttoikä h	Valovirta lm 25°C	Pakkaus- koko	Tuote- numero	SSTL
ILCOS: FDH		ZWEI: T5	Värintoistoluokka 1B		Kanta G5			
24	549	F24T5/827	2700	30.000	1818	30	90262	49 844 27
24	549	F24T5/830	3000	30.000	1818	30	90263	49 844 30
24	549	F24T5/835	3500	30.000	1818	30	90264	49 844 35
24	549	F24T5/840	4000	30.000	1818	30	90265	49 844 40
24	549	F24T5/865	6500	30.000	1818	30	90266	49 844 65
39	849	F39/T5/827	2700	30.000	3182	30	90267	49 845 27
39	849	F39/T5/830	3000	30.000	3182	30	90268	49 845 30
39	849	F39/T5/835	3500	30.000	3182	30	90269	49 845 35
39	849	F39/T5/840	4000	30.000	3182	30	90270	49 845 40
39	849	F39/T5/865	6500	30.000	3182	30	90271	49 845 65
54	1149	F54T5/827	2700	30.000	4545	30	90272	49 846 27
54	1149	F54T5/830	3000	30.000	4545	30	90273	49 846 30
54	1149	F54T5/835	3500	30.000	4545	30	90274	49 846 35
54	1149	F54T5/840	4000	30.000	4545	30	90275	49 846 40
54	1149	F54T5/865	6500	30.000	4545	30	90276	49 846 65
49	1449	F49T5/830	3000	30.000	4455	30	90278	49 847 30
49	1449	F49T5/835	3500	30.000	4455	30	90279	49 847 35
49	1449	F49T5/840	4000	30.000	4455	30	90280	49 847 40
49	1449	F49T5/865	6500	30.000	4455	30	90281	49 847 65
80	1449	F80T5/830	3000	30.000	6364	30	90283	49 848 30
80	1449	F80T5/835	3500	30.000	6364	30	90284	49 848 35
80	1449	F80T5/840	4000	30.000	6364	30	90285	49 848 40
80	1449	F80T5/865	6500	30.000	6364	30	90286	49 848 65



A

B

C

D

E

F

G

H

I

J

K

Loistelamput

T5 Watt-Miser™ loistelamput- energiansäästö yli 5%



Teho W	Pituus mm	Nimike	Väriämpötila K	Keskim polttoikä h	Valovirta lm 25°C	Pakkaus-koko	Tuote-numero	SSTL
ILCOS: FDH			ZWEI: T5		Värintoistoluokka 1B		Kanta G5	
14	549	F14T5/830WM	3000	25.000	1227	30	88364	49 850 01
14	549	F14T5/835WM	3500	25.000	1227	30	88363	49 850 02
14	549	F14T5/840WM	4000	25.000	1227	30	88362	49 850 03
14	549	F14T5/865WM	6500	25.000	1227	30	88361	49 850 04
21	849	F21T5/830WM	3000	25.000	1909	30	88360	49 850 05
21	849	F21T5/835WM	3500	25.000	1909	30	88358	49 850 06
21	849	F21T5/840WM	4000	25.000	1909	30	88357	49 850 07
21	849	F21T5/865WM	6500	25.000	1909	30	88359	49 850 08
28	1149	F28T5/830WM	3000	25.000	2636	30	88345	49 850 09
28	1149	F28T5/835WM	3500	25.000	2636	30	88346	49 850 10
28	1149	F28T5/840WM	4000	25.000	2636	30	88356	49 850 11
28	1149	F28T5/865WM	6500	25.000	2636	30	88341	49 850 12
35	1449	F35T5/830WM	3000	25.000	3318	30	88355	49 850 13
35	1449	F35T5/835WM	3500	25.000	3318	30	88342	49 850 14
35	1449	F35T5/840WM	4000	25.000	3318	30	88354	49 850 15
35	1449	F35T5/865WM	6500	25.000	3318	30	88353	49 850 16
24	549	F24T5/830WM	3000	25.000	1818	30	88352	49 850 17
24	549	F24T5/835WM	3500	25.000	1818	30	88351	49 850 18
24	549	F24T5/840WM	4000	25.000	1818	30	88350	49 850 19
24	549	F24T5/865WM	6500	25.000	1818	30	88349	49 850 20
39	849	F39/T5/830WM	3000	25.000	3182	30	88348	49 850 21
39	849	F39/T5/835WM	3500	25.000	3182	30	88347	49 850 22
39	849	F39/T5/840WM	4000	25.000	3182	30	88344	49 850 23
39	849	F39/T5/865WM	6500	25.000	3182	30	88334	49 850 24
54	1149	F54T5/830WM	3000	25.000	4545	30	88328	49 850 25
54	1149	F54T5/835WM	3500	25.000	4545	30	88338	49 850 26
54	1149	F54T5/840WM	4000	25.000	4545	30	88337	49 850 27
54	1149	F54T5/865WM	6500	25.000	4545	30	88333	49 850 28
49	1449	F49T5/830WM	3000	25.000	4455	30	88343	49 850 29
49	1449	F49T5/835WM	3500	25.000	4455	30	88339	49 850 30
49	1449	F49T5/840WM	4000	25.000	4455	30	88336	49 850 31
49	1449	F49T5/865WM	6500	25.000	4455	30	88340	49 850 32



T5 Watt-Miser™ loistelamput- energiansäästö yli 5%

Teho W	Pituus mm	Nimike	Värieläpötila K	Keskim polttoikä h	Valovirta lm 25°C	Pakkaus-koko	Tuote-numero	SSTL
ILCOS: FDH		ZWEI: T5	Värintoistoluokka 1B		Kanta G5			
80	1449	F80T5/830WM	3000	25.000	6364	30	88329	49 850 33
80	1449	F80T5/835WM	3500	25.000	6364	30	88330	49 850 34
80	1449	F80T5/840WM	4000	25.000	6364	30	88332	49 850 35
80	1449	F80T5/865WM	6500	25.000	6364	30	88331	49 850 36


Cov-R-Guard™ suojapinnoitetut T5 loistelamput

24		F24W/T5/830/ECO/CVG	3000	20.000	2000	40	71000	49 850 40
24		F24W/T5/835/ECO/CVG	3500	20.000	2000	40	70998	49 850 41
24		F24W/T5/841/ECO/CVG	4100	20.000	2000	40	70997	49 850 42
24		F24W/T5/850/ECO/CVG	5000	20.000	2000	40	70999	49 850 43
24		F24W/T5/865/ECO/CVG	6500	20.000	1900	40	70996	49 850 44
39		F39W/T5/830/ECO/CVG	3000	20.000	3500	40	70995	49 850 45
39		F39W/T5/835/ECO/CVG	3500	20.000	3500	40	70994	49 850 46
39		F39W/T5/841/ECO/CVG	4100	20.000	3500	40	70993	49 850 47
39		F39W/T5/850/ECO/CVG	5000	20.000	3500	40	70991	49 850 48
39		F39W/T5/865/ECO/CVG	6500	20.000	3330	40	70990	49 850 60
54		F54W/T5830HOECO/CVG	3000	20.000	5000	40	48433	49 850 61
54		F54W/T5835HOECO/CVG	3500	20.000	5000	40	48436	49 850 62
54		F54W/T5840HOECO/CVG	4100	20.000	5000	40	48458	49 850 63
54		F54W/T5850HOECO/CVG	5000	20.000	5000	40	80311	49 850 64
54		F54W/T5865HOECO/CVG	6500	20.000	4750	40	48469	49 851 01


Circline® - T5 rengasloistelamput 2GX13

22	225	FC22T5/827	2700	12.000	1800	10	75707	49 834 35
22	225	FC22T5/830	3000	12.000	1800	10	75709	49 834 36
22	225	FC22T5/840	4000	12.000	1800	10	75710	49 834 37
22	225	FC22T5/865	6500	12.000	1670	10	75711	49 834 38
40	300	FC40T5/827	2700	12.000	3300	10	75712	49 834 39
40	300	FC40T5/830	3000	12.000	3300	10	75713	49 83 440
40	300	FC40T5/840	4000	12.000	3300	10	75715	49 834 41
40	300	FC40T5/865	6500	12.000	3000	10	75716	49 834 42
55	300	FC55T5/827	2700	12.000	4000	10	75717	49 834 43
55	300	FC55T5/830	3000	12.000	4000	10	75718	49 834 44
55	300	FC55T5/840	4000	12.000	4000	10	75719	49 834 45
55	300	FC55T5/865	6500	12.000	3640	10	75720	49 834 46



T8 Polylux XLr™ kolmihiippuloistelamput, Ra85 - 26 mm halkaisija

Teho W	Pituus mm	Nimike	Väriämpötila K	Keskim polttoikä h	Valovirta lm 25°C	Pakkaus-koko	Tuote-numero	SSTL
ILCOS: FD			ZWEI: T8		Värintoistoluokka 1B		Kanta G13	
15	450	F15/827	2700	20.000	1000	25	23247	49 808 27
15	450	F15/830	2950	20.000	1000	25	23248	49 808 30
15	450	F15/840	4000	20.000	1000	25	23249	49 808 40
18	600	F18/827	2700	20.000	1350	25	93315	49 803 27
18	600	F18/830	2950	20.000	1350	25	93319	49 803 30
18	600	F18/835	3400	20.000	1350	25	93311	49 803 35
18	600	F18/840	4000	20.000	1350	25	93317	49 803 40
18	600	F18/860	6300	20.000	1300	25	12606	49 803 60
30	900	F30/827	2700	20.000	2450	25	18138	49 810 27
30	900	F30/830	2950	20.000	2450	25	18141	49 810 30
30	900	F30/840	4000	20.000	2450	25	18142	49 810 40
36	1200	F36/827	2700	20.000	3350	25	19977	49 805 27
36	1200	F36/830	2950	20.000	3350	25	18192	49 805 30
36	1200	F36/835	3400	20.000	3350	25	19991	49 805 35
36	1200	F36/840	4000	20.000	3350	25	16856	49 805 40
36	1200	F36/860	6300	20.000	3250	25	12942	49 805 60
58	1500	F58/827	2700	20.000	5200	25	93330	49 806 27
58	1500	F58/830	2950	20.000	5200	25	93334	49 806 30
58	1500	F58/835	3400	20.000	5200	25	93331	49 806 35
58	1500	F58/840	4000	20.000	5200	25	93333	49 806 40
58	1500	F58/860	6300	20.000	5000	25	12943	49 806 60

T8 Polylux XLr™ Long Last loistelamput - polttoikä 42000 h

ILCOS: FD			ZWEI: T8		Värintoistoluokka 1B		Kanta G13	
18		F18/830 /LL	2950	42.000	1350	25	70980	49 835 47
18		F18/840 /LL	4040	42.000	1350	25	70981	49 835 48
36		F36/830 /LL	2950	42.000	3350	25	43508	49 835 40
36		F36/840 /LL	4040	42.000	3350	25	43509	49 835 42
58		F58/830 /LL	2950	42.000	5200	25	43510	49 835 44
58		F58/840 /LL	4040	42.000	5200	25	43511	49 835 46
70		F70/830 /LL	2950	42.000	6300	25	43513	
70		F70/840 /LL	4040	42.000	6300	25	43514	



T8 Watt-Miser™ loistelamput- energiansäästö yli 10%

Teho W	Pituus mm	Nimike	Väriämpötila K	Keskim polttoikä h	Valovirta lm 25°C	Pakkaus-koko	Tuote-numero	SSTL
T8 Watt-Miser™ energiansäästö kolmihiippuloistelamput, Ra85								
ILCOS: FD		ZWEI: T8	Värintoistoluokka 1B					
16	600	F18/830 WM 16W	3000	20.000	1320	25	73605	49 851 02
16	600	F18/835 WN 16W	3500	20.000	1320	25	73606	49 851 03
16	600	F18/840 WM 16W	4000	20.000	1320	25	73607	49 851 04
16	600	F18/860 WM 16W	6400	20.000	1250	25	73608	49 851 05
32	1200	F36/830 WM 32W	3000	20.000	2925	25	96748	49 851 06
32	1200	F36/835 WM 32W	3500	20.000	2925	25	96749	49 851 07
32	1200	F36/840 WM 32W	4000	20.000	2925	25	96750	49 851 08
32	1200	F36/860 WM 32W	6400	20.000	2925	25	96747	49 851 09
51	1500	F58/830 WM 51W	3000	20.000	4600	25	73609	49 851 10
51	1500	F58/835 WM 51W	3500	20.000	4600	25	73610	49 851 11
51	1500	F58/840 WM 51W	4000	20.000	4600	25	73611	49 851 12
51	1500	F58/860 WM 51W	6400	20.000	4420	25	73613	49 851 13



Cov-R-Guard™ suojapinnoitetut Polylux XLr loistelamput, kanta G13

ILCOS: FD		ZWEI: T8	Värintoistoluokka 1B			Kanta G13		
18	600	F18/830/CVG/XLr	2950	20.000	1300	25	17203	49 840 02
18	600	F18/835/CVG/XLr	3400	20.000	1300	25	17204	49 840 03
18	600	F18/840/CVG/XLr	4000	20.000	1300	25	17205	49 840 04
36	1200	F36/830/CVG/XLr	2950	20.000	3250	25	17208	49 840 12
36	1200	F36/835/CVG/XLr	3400	20.000	3250	25	17202	49 840 13
36	1200	F36/840/CVG/XLr	4000	20.000	3250	25	17209	49 840 14
58	1500	F58/830/CVG/XLr	2950	20.000	5050	25	12403	49 840 22
58	1500	F58/835/CVG/XLr	3400	20.000	5050	25	12405	49 840 23
58	1500	F58/840/CVG/XLr	4000	20.000	5050	25	12407	49 840 24



T8 Erikoispituus



T8 Erikoispituus 970 mm - 26 mm halkaisija

Teho W	Pituus mm	Nimike	Väriämpötila K	Keskim polttoika h	Valovirta lm 25°C	Pakkaus-koko	Tuote-numero	SSTL
ILCOS: FD			ZWEI: T8		Värintoistoluokka 2B		Kanta G13	
36	970	F36M/830	2950	16.000	3100	25	23260	49 823 46
36	970	F36M/840	4000	16.000	3100	25	23262	49 823 47

T12 Vakioloistelamput - 38 mm halkaisija

ILCOS: FD			ZWEI: T12		Värintoistoluokka 2B		Kanta G13	
20	600	F20/35	3450	9.000	1150	25	29748	49 801 12
20	600	F20/33	4200	9.000	1150	25	29746	49 801 04
20	600	F20/33RS	4200	9.000	1100	25	29758	49 815 04
40	1200	F40/35	3450	9.000	2950	25	29769	49 804 12
40	1200	F40/33	4200	9.000	2950	25	29765	49 804 04
40	1200	F40/29RS	2950	9.000	2900	25	29776	49 815 58
40	1200	F40/33RS	4200	9.000	2900	25	29775	49 815 54
65/80	1500	F65/35	3450	9.000	4750	25	72691	49 808 12
65/80	1500	F65/33	4200	9.000	4750	25	72692	49 808 04
65/80	1500	F65/33RS	4200	9.000	4700	25	29791	49 815 79

Circline® -rengasloistelamput, kanta G10q



ILCOS: FC			ZWEI: T9-C		Värintoistoluokka 2B			
22	215,9	FC8T9/CW	4040	5.000	1000	12	10455	49 834 11
32	304,8	FC12T9/CW	4040	5.000	1825	12	10462	49 834 21
40	406,4	FC16T9/CW	4040	5.000	2700	12	10474	49 834 31

Pienloistelamput - 16 mm halkaisija



ILCOS: FD			ZWEI: T5		Värintoistoluokka 3		Kanta G5	
4	150	F4/35	3450	5.000	130	25	39446	49 823 04
4	150	F4/33	4040	5.000	130	25	39441	49 823 01
6	225	F6/35	3450	5.000	260	25	39442	49 823 24
6	225	F6/33	4040	5.000	260	25	39445	49 823 21
8	300	F8/29	2940	5.000	385	25	37754	49 823 52
8	300	F8/35	3450	5.000	385	25	37756	49 823 54
8	300	F8/33	4040	5.000	385	25	37755	49 823 51
13	525	F13/29	2940	6.000	850	25	12684	49 823 72
13	525	F13/35	3450	6.000	850	25	12694	49 823 74
13	525	F13/33	4040	6.000	850	25	12693	49 823 71

T5 Pienisloistelamppu

Teho W	Pituus mm	Nimike	Värlämpötila K	Keskim polttoikä h	Valovirta lm 25°C	Pakkaus-koko	Tuote-numero	SSTL
Pienisloistelamppu Specsfill, HF käyttöön								
6	225	F6/33 Teollisuuspakkaus	4000	8.000	260	100	40307	
6	225	F6/840 teollisuuspakkaus	4000	8.000	300	100	40327	
8	300	F8/35	3450	8.000	400	25	27027	
8	300	F8/33	4000	8.000	400	25	27011	
8	300	F8/840 teollisuuspakkaus	4000	8.000	470	100	37009	



Power Groove® -loistelamppu, 54 mm halkaisija, kanta R17d

Värintoistoluokka 2B

215	2440	F96PG17/CW 215W	4100	10.000	15300	8	11009	49 813 23
-----	------	-----------------	------	--------	-------	---	-------	-----------



Mustavalololoistelamppu Kanta G13

20	600	F20W/BLB		9.000		6	34747	49 861 06
40	1200	F40T12/BLB		9.000		6	25618	49 861 10
18	600	F18T8/BLB		12.000		25	88832	49 851 14
36	1200	F36T8/BLB		12.000		25	88833	49 851 15



Mustavalololoistelamppu Kanta G5

4	150	F4W/BLB		5.000		25	39882	49 861 14
6	225	F6W/BLB		5.000		25	39883	49 861 16
8	300	F8W/BLB		5.000		25	39884	49 861 18

Germicidal Desinfektiolamput

Teho W	Pituus mm	Nimike	Väriämpötila K	Keskim polttoika h	Valovirta lm 25°C	Pakkaus-koko	Tuote-numero	SSTL
Germicidal Desinfektiolamput, UVC 253,7nm								
6	225	G6T5 G5	G5	6.000	1,7	24	15873	49 841 52
8	300	G8T5 G5	G5	8.000	2,3	24	11077	49 841 54
15	450	G15T8 G13	G13	8.000	4,8	24	11078	49 841 56
30	910	G30T8 G13	G13	8.000	12,4	24	11080	49 841 58
36	1200	G36T8 G13	G13	8.000	14,6	24	29504	49 841 60



Germicidal Biax™ Desinfektiolamput, UVC 253,7nm

5	85	GBX5/UVC	G23	8.000	1,2	10	40695	49 841 64
9	145	GBX9/UVC	G23	8.000	2,4	10	40696	49 841 66
11	215	GBX11/UVC	G23	8.000	3,6	10	40700	49 841 68
18	225	GBX18/UVC	2G11	8.000	5,5	10	40704	49 841 70
36	415	GBX36/UVC	2G11	8.000	12	10	40705	49 841 72
55	535	GBX55/UVC	2G11	8.000	17	10	40706	49 841 74



Loistelampun sytyttimet

15-22	155/200 15-22W	25/250	36711	40 450 00
15-22	155/200 Bulk	2000	36714	40 450 01
4-65	155/500 4-65W	25/250	36536	40 450 02
4-65	155/500 Bulk	2000	36537	40 450 03
75-125	155/800 75-125W	250	37864	40 450 04
4-65	155/400 2D	25/500	17163	

