nVent ERICO Cadweld Plus Impulse Exothermic Welding Control Unit



CONNECT AND PROTECT

Our latest innovation, **nVent ERICO Cadweld Plus Impulse Exothermic Welding Control Unit**, brings you the highest level of flexibility and ease of use of any of our ignition systems. Precision engineered, the control unit lets you choose your power source: from off-the-shelf AA-batteries to the rechargeable Lithium-lon packs you have on your job site.

Why should you choose our latest ignition system? Safety, power and ease-of-use.

SAFETY

- Self-closing trigger guard prevents accidental ignition, providing added safety
- LED ignition counter provides instant feedback on the timing of the ignition and is visibile in sunny outdoor conditions
- Five second delay in ignition is a safety feature to allow the user to stop ignition, if necessary

POWER

- Battery life indicator integrated into the unit for real-time updates on battery life; compatible with both AA and rechargeable batteries
- Includes AA alkaline batteries to power approximately 600 connections
- Rechargeable batteries from Milwaukee® or DEWALT® can be used to power approximately 1500 connections using a 4Ah battery
- Battery adapters available for use with either Milwaukee® or DEWALT® rechargeable batteries (sold separately)

EASE-OF-USE

- High temperature lead with single molded insert into the control unit keeps the most-often replaced component of ignition systems more securely attached and reliable
- Easy-to-use alligator clip design of the termination clearly shows a positive connection in the viewing window
- Enhanced power tool style grip is ergonomic and easy to hold



Part Number	Cable Length	Batteries	Working Temperature
PLUSCU2L6	1.8 m	8 Standard AA Batteries	-18°C - 54°C
PLUSCU2L15	4.5 m	8 Standard AA Batteries	−18°C − 54°C

RICO-DS-H85758-Cadweldimpulse-UKEN-2006 nVent.com/ERICO | 1










Part Number	Item Description	Control Unit	Leads	AA Batteries	Battery Adapter
PLUSCU2L6	Control Unit with 1.8 m Lead	Base Control Unit	1.8 m length	8 Alkaline	For AA batteries
PLUSCU2L15	Control Unit with 4.5 m Lead	Base Control Unit	4.5 m length	8 Alkaline	For AA batteries
PLUSCU2RLD6	Replacement Lead, 1.8 m		1.8 m length		
PLUSCU2RLD15	Replacement Lead, 4.5 m		4.5 m length		
PLUSCU2BAA AA Battery Ao	AA Battery Adapter				For AA batteries
PLUSCU2BM	Milwaukee® Battery Adapter				For Milwaukee® 18V rechargable batteries
PLUSCU2BD	DEWALT® Battery Adapter				For DEWALT® 20V rechargable batteries

The control unit is part of the nVent ERICO Cadweld family, which includes:

- 1. Standard and custom exothermic mold configurations
- 2. Welding material
- 3. Tools and accessories





For more information, visit cadweld.com or contact your sales representative.

Include business contact information here.



Our powerful portfolio of brands:

RAYCHEM