

Tuotetiedot


Tuotekoodi	VA02-0056	Sähkönumero	5201787	EAN-koodi	6430051862373
Tuotenimi	PKD-putkikaapelikengä 185-24			ETIM-luokka	EC001051
Johtimet	Cu 185 mm ²				

Tekniset tiedot

	-	
	-	
	-	
	-	
	-	
	-	
	-	
Napaluku	1	kpl
Max. Johdinkoko	185	mm ²
	-	
	-	
	-	
	-	
	-	
	-	
Paino	140	g
	-	
	-	
Väri / Materiaali	Tinapinnoitettu kupari	
Kiinnitys / Kytentä	Puristus	


Kuvaus

PKD-kaapelikengät valmistetaan 99,9 % puhtaasta kuparista ja pinnoitetaan elektrolyttisesti tinalla. Liittimien asennus voidaan suorittaa yleisimmillä puristustyökaluilla. Puristettavat putkikaapelikengät on tarkoitettu Cu-kaapeleiden sekä käämien, johtimien ja kiskojen päättämiseen, kytkemiseen ja haaroittamiseen. PKD-sarjan kaapelikengät soveltuvat harvasäikeisille tiivistetyille johtimille.

Mittakuva

Pakkaus

Pakkausmuoto	Laatikko	Kpl / Pakkaus	25	Paino [kg]	3,50
Pituus [mm]	176	Leveys [mm]	141	Korkeus [mm]	80

Ouneva Oy

Teollisuustie 21
FI-82730 Tuupovaara
Finland

Tel. +358 400 179 750
info@ouneva.fi

www.ounevagroup.fi
www.ounevaproducts.fi

Product data


Product code	VA02-0056	STK-code	5201787	EAN-code	6430051862373
Product name	PKD cable lug 185-24			ETIM class	EC001051
Wires	Cu 185 mm ²				

Technical data

	-	
	-	
	-	
	-	
	-	
	-	
	-	
Number of poles	1	pcs
Max. Cross section	185	mm ²
	-	
	-	
	-	
	-	
	-	
	-	
Weight	140	g
	-	
	-	
Color / Material	Tin plated copper	
Mounting / Connection	Crimping	


Description

Ouneva PKD-series copper cable lugs are designed for connecting copper cables, coils and busbars. The lugs are manufactured of 99,9 % pure copper and electrolytically coated with tin. Installation of the cable lugs can be performed with the most basic crimping tools. PKD-series cable lugs are compatible with compressed stranded wires.

Drawing

Package

Package	Box	Pcs / Package	25	Weight [kg]	3,50
Length [mm]	176	Width [mm]	141	Height [mm]	80

Ouneva Oy

Teollisuustie 21
 FI-82730 Tuupovaara
 Finland

Tel. +358 400 179 750
info@ouneva.fi

www.ounevagroup.fi
www.ounevaproducts.fi