


DSH TNS 255 (941 400)


- Application-optimised prewired spark-gap-based combined lightning current and surge arrester
- Space-saving arrester for compact and simply equipped electrical installations with reduced technical requirements
- Capable of protecting terminal equipment



Figure without obligation



Basic circuit diagram DSH TNS 255



Dimension drawing DSH TNS 255

Application-optimised prewired combined lightning current and surge arrester for TN-S systems

| Type | DSH TNS 255 |
|----------------------------------------------------------------------------|----------------------------------------------------------------------|
| Part No. | 941 400 |
| SPD according to EN 61643-11 / IEC 61643-1-11 | Type 1 / Class I |
| Energy coordination with terminal equipment | Type 1 + Type 2 |
| Energy coordination with terminal equipment (≤ 5 m) | Type 1 + Type 2 + Type 3 |
| Nominal a.c. voltage (U_N) | 230 / 400 V |
| Max. continuous operating a.c. voltage (U_c) | 255 V |
| Lightning impulse current (10/350 μ s) [L1+L2+L3+N-PE] (I_{total}) | 50 kA |
| Specific energy [L1+L2+L3+N-PE] (W/R) | 625.00 kJ/ohms |
| Lightning impulse current (10/350 μ s) [L, N-PE] (I_{imp}) | 12.5 kA |
| Specific energy [L,N-PE] (W/R) | 39.06 kJ/ohms |
| Nominal discharge current (8/20 μ s) (I_n) | 12.5 / 50 kA |
| Voltage protection level [L-PE]/[N-PE] (U_p) | $\leq 1.5 / \leq 1.5$ kV |
| Follow current extinguishing capability a.c. (I_h) | 25 kA _{rms} |
| Follow current limitation>Selectivity | no tripping of a 32 A gL/gG fuse up to 25 kA _{rms} (prosp.) |
| Response time (t_A) | ≤ 100 ns |
| Max. mains-side overcurrent protection | 160 A gL/gG |
| Temporary overvoltage (TOV) [L-N] (U_T) | 440 V / 5 sec. |
| TOV characteristic | withstand |
| Operating temperature range (T_u) | -40 °C...+80 °C |
| Operating state/fault indication | green / red |
| Number of ports | 1 |
| Cross-sectional area (L1, L2, L3, N, PE, \pm) (min.) | 1.5 mm ² solid/flexible |
| Cross-sectional area (L1, L2, L3, N, PE, \pm) (max.) | 35 mm ² stranded/25 mm ² flexible |
| For mounting on | 35 mm DIN rails acc. to EN 60715 |
| Enclosure material | thermoplastic, red, UL 94 V-0 |
| Place of installation | indoor installation |
| Degree of protection | IP 20 |
| Capacity | 4 module(s), DIN 43880 |
| Approvals | KEMA |
| Weight | 525 g |
| Customs tariff number | 85363030 |
| GTIN | 4013364133563 |
| PU | 1 pc(s) |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.