


DPI CD EXD 24 M (929 962)


- Easy to mount on the spare cable gland of field devices
- Ex(d) type for universal use
- For installation in conformity with the lightning protection zone concept at the boundaries from $0_B - 2$ and higher



Figure without obligation



Basic circuit diagram DPI CD EXD 24 M



Dimension drawing DPI CD EXD 24 M

Flameproof surge arrester with a low-capacitance protective circuit for protecting measuring circuits and bus systems in potentially explosive atmospheres. Insulation strength > 500 V to earth. Certified to CSA and USA Hazloc standards.

Technical data

Type	DPI CD EXD 24 M
Part No.	929 962
SPD class	TYPE 2 PI
Nominal voltage (U_N)	24 V
Max. continuous operating voltage (d.c.) (U_C)	32 V
Max. continuous operating voltage (a.c.) (U_C)	22.6 V
Nominal current (I_L)	0.55 A
D1 Lightning impulse current (10/350 μ s) line-PG (I_{imp})	1 kA
C2 Total nominal discharge current (8/20 μ s) (I_n)	10 kA
C2 Nominal discharge current (8/20 μ s) per line (I_n)	10 kA
Voltage protection level line-line for I_n C2 (U_p)	≤ 58 V
Voltage protection level line-PG for I_n C2 (U_p)	≤ 1700 V
Voltage protection level line-line at 1 kV/ μ s C3 (U_p)	≤ 50 V
Voltage protection level line-PG at 1 kV/ μ s C3 (U_p)	≤ 1200 V
Cut-off frequency line-line (f_c)	67 MHz
Capacitance line-line (C)	≤ 25 pF
Capacitance line-PG (C)	≤ 15 pF
Operating temperature range (T_U)	-50 °C ... +80 °C
Degree of protection	IP 67
For mounting on (field / device side)	M20 x 1.5 male thread
Connection	connecting lines (1.3 mm ²)
Length of the connecting lead	250 mm
Earthing via	connecting line
Enclosure material	StSt (V4A)
Colour	bare surface
Test standards	IEC 61643-21 / EN 61643-21
Approvals	EACEx, ATEX, IECEx, CSA & USA Hazloc, SIL
ATEX approvals	KEMA 04ATEX2190 X: II 2 G Ex d IIC T5 or T6 Gb
IECEx approvals	KEM 09.0064X: Ex d IIC T5 or T6 Gb
CSA & USA Hazloc approvals (1)	CSA 10.2317168: Ex d IIC T4 ... T6
CSA & USA Hazloc approvals (2)	CSA 10.2317168: Class I Div 1, 2; Class I Zone 1
SIL classification	up to SIL3 ^{*)}
Weight	169 g
Customs tariff number (Comb. Nomenclature EU)	85363010
GTIN	4013364101791
PU	1 pc(s)

*) For more detailed information, please visit www.dehn-international.com.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.