

## HH-SICHERUNG IKUS 10-32/ 8N 12KV/32A 292X53 80N

Article number: Q3152902



(Illustration similar)

### Description

Back-up fuse-links for short circuit protection of transformers up to 12kV according to IEC 60282-1 respectively DIN EN 60282-1 and DIN VDE 0670-402.

### Features

|                                                     |                                                                               |
|-----------------------------------------------------|-------------------------------------------------------------------------------|
| <b>Class</b>                                        | Back-Up                                                                       |
| <b>Rated voltage AC</b>                             | 12kV                                                                          |
| <b>Permissible minimum operating voltage</b>        | 6kV                                                                           |
| <b>Length "e"</b>                                   | 292mm                                                                         |
| <b>Diameter</b>                                     | 53mm                                                                          |
| <b>Rated current</b>                                | 32A                                                                           |
| <b>Minimum breaking current</b>                     | 130A                                                                          |
| <b>Striker</b>                                      | 80N - medium type                                                             |
| <b>Operating Joule integral at <math>U_n</math></b> | 10100A <sup>2</sup> s                                                         |
| <b>Pre-arcing Joule integral</b>                    | 1220A <sup>2</sup> s                                                          |
| <b>Power dissipation at rated current</b>           | 45.6W                                                                         |
| <b>Rated breaking capacity AC</b>                   | 63kA                                                                          |
| <b>Application</b>                                  | <ul style="list-style-type: none"> <li>• Indoor</li> <li>• Outdoor</li> </ul> |

Further developments of our products and technical changes are subject to change. Alterations, errors and errata constitute no claim for damages. Our valid sales terms and delivery conditions are available on our website <http://www.jeanmueller.de>

Printed at: 12.01.2016 / 14:21