



APT 48 (785 780)



Figure without obligation

- Knee pads and pair of braces included
- Pockets for knee pads
- Adjustable belt

| Type                                               | APT 48                                                     |
|----------------------------------------------------|------------------------------------------------------------|
| Part No.                                           | 785 780                                                    |
| Direct incident energy (E <sub>io</sub> )          | (class 2 / 7 kA, 500 ms) 423 kJ / m <sup>2</sup>           |
| Extended direct incident energy (E <sub>io</sub> ) | (class 2*) 1050 ... 1390 kJ / m <sup>2</sup>               |
| Arc energy (W <sub>arc</sub> )                     | 318 kJ                                                     |
| ATPV (Arc Thermal Performance Value)               | 29.2 cal / cm <sup>2</sup>                                 |
| Size                                               | 48                                                         |
| Outer material                                     | Siliconised calf grain leather, 100% Kevlar interlock knit |
| Inner material                                     | 100% cotton                                                |
| Material (sewing thread)                           | 100% Kevlar                                                |
| Standard                                           | Box test in accordance with IEC 61482-1-2, EN ISO 14116    |
| Weight                                             | 1,54 kg                                                    |
| Customs tariff number                              | 42031000                                                   |
| GTIN                                               | 4013364149526                                              |
| PU                                                 | 1 pc(s)                                                    |

\*<sup>1</sup>) The distance of the specimen was reduced from 300 mm to 150 mm based on IEC 61482-1-2.  
If the protective trousers are heavily soiled, they can be dry cleaned in a leather cleaner's.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.