

# **3M<sup>™</sup> E-A-R<sup>™</sup> Express<sup>™</sup> Earplugs**

## **Key benefits:**



## Protective

- Foams an effective seal at the entrance of the ear canal
- Compatible with 3M<sup>™</sup> E-A-RFit<sup>™</sup> Dual Ear Validation System which measures the effectiveness of the earplug's protection level
- Plugs are kept hygienic and clean with no roll down required

28dB SNR 87dB-98dB (A)

Suggested for noise levels within this range.

## **Attenuation values**

Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
Mf (dB)	27.8	26.0	24.9	25.2	29.4	34.9	37.0	35.9
sf (dB)	5.4	4.5	3.3	5.0	4.2	4.1	5.2	3.7
APVf (dB)	22.4	21.5	21.5	20.2	25.2	30.8	31.8	32.2
SNR = 28dB. H = 30dB. M = 24dB. L = 22dB.								

#### Key

<b>APVf (dB)</b> = Mf –sf (dB)		
Mf = Mean		
attenuation value		
<b>sf</b> = Standard deviation		
APVf = Assumed		
protection value		

 H = High-frequency attenuation value
M = Medium-frequency attenuation value
L = Low-frequency attenuation value **SNR** = Single number rating (the value that is subtracted from the measured C-weighted sound pressure level, L(C) in order to estimate the effective A-weighted sound pressure level inside the ear)

## Convenient

- Available in both corded and uncorded versions
- No roll-down required a gentle push is all it takes for easy, consistent insertion
- Semi flexible stem helps easy insertion and removal

## Comfortable

- Patented E-A-R<sup>™</sup> foam tips which are shaped and sized to mould comfortably to the ear
- Slow expanding foam with a low pressure seal for improved comfort

## **Materials**

The following materials are used in the manufacture of this product:

Component	Material
Earplugs	Polyurethane foam
Cord	PVC
Stem	PVC

## Ordering information

Short ID	Description				
3M <sup>™</sup> E-A-R <sup>™</sup> Express Pod Plugs					
EX01002	3M <sup>™</sup> E-A-R <sup>™</sup> Express <sup>™</sup> Earplugs				
EX01001	3M <sup>™</sup> E-A-R <sup>™</sup> Express <sup>™</sup> Earplugs corded				
3M <sup>™</sup> E-A-RFit <sup>™</sup> Dual Ear Validation System					
393-1100	E-A-RFit Dual Ear Validation System				
EXPRESSP	3M <sup>™</sup> E-A-R <sup>™</sup> Express <sup>™</sup> probed test plug				

#### **Personal Safety Division**

**3M United Kingdom PLC** 3M Centre, Cain Road, Bracknell Berkshire RG12 8HT t: 0870 60 800 60 www.3M.co.uk/safety **3M Ireland Limited** The Iveagh Building The Park Carrickmines Dublin 18

Please recycle. Printed in the UK. © 3M 2019. 3M, E-A-R, E-A-RFit and Express are trademarks of 3M Company. Used under licence by 3M subsidiaries and affiliates. All rights reserved. J458016