



DIESEL 15000 TE XL C

Product advantages

- ➡ Entire group guaranteed 3 years
- ➡ KOHLER Professional Engine
- ➡ Electric starter with batteries without maintenance
- Connection interface equipped with an hour meter
- ➡ Very large Autonomy















DIESEL 15000 TE XL C

General specifications

| Range | Diesel |
|-------------------------------------|---------------------|
| Frequency (Hz) | 50 |
| Max. power (LTP) (kW) | 10.00 |
| Max power. (LTP) (kVA) | 12.50 |
| Nominal voltage (V) | 400 |
| Number of phase | Three phase - 400 V |
| Guaranteed acoustic power Lw | 109 |
| Noise level dB(A) - 7m | 80 |

Engine specifications

| Engine trademark | Kohler Diesel |
|--------------------|---------------|
| Engine type | KD425-2 |
| Distribution | Fuel O.H.V. |
| Start | Electrical |
| Fuel | Fuel |
| Autonomy (h) | 16.7 |
| Comsumption (L/h] | 2.1 |
| Tank (L) | 35 |
| Oil Guard | Yes |
| HP 3600 tr/mn max. | 19 |
| Capacity (cm3) | 851 |
| Oil capacity (L) | 1.8 |
| | |

Alternator specifications

| Туре | With collar and brush |
|------------------|-----------------------|
| Regulation | Mechanical |
| Protection class | IP 23 |
| Insulation class | Н |

Plugs and panels descriptive

1 230V 10/16A socket - circuit breaker + 1 230V 16A socket - circuit breaker + 1 400V 16A socket - circuit breaker + hour meter + indicator + MICS MODYS(2)

Dimensions and weight

| Lenght (cm) | 89.5 |
|------------------|------|
| Width (cm) | 57 |
| Height (cm) | 77 |
| Dry Weight (kgs) | 169 |

Packaging

| Packaging type | Box / Pallet |
|-------------------------|--------------|
| Length (cm) | 91 |
| Width (cm) | 58.5 |
| Height (cm) | 92 |
| Number of box by pallet | 0 |
| Pallet height (cm) | 0 |



DIESEL 15000 TE XL C

Delivered accessories

User and maintenance manual

Options

| R03B | Differencial protection R03B | This set includes a differential switch, a hour meter, the plugs and a thermal circuit breaker. |
|------|--|---|
| R05A | Automatic start mains failure panel R05A | Automatic start, remote control, start on dry contact. |
| RPM | | Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V |
| RPQ | • | For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm ² cable. |
| R05A | Automatic start mains failure panel R05A | Automatic start, remote control, start on dry contact. |
| RKB2 | #Kit brouette RKB2 | Trolley kit for the generating sets superior to 6kW |