



## TR 3.60 H

### Product advantages

- ➡ Easy access to the turbine
- ➡ OHV Honda professional engine
- ➡ Oil level safety
- ➡ Helix and impeller in graphic cast iron
- ➡ Mechanic seal in ceramic carbon

### Miscellaneous

For frequent use, heavy duty professional applications.

## TR 3.60 H

### General specifications

Range	Intens Aqualine
-------	-----------------

### Water pumps specifications

Suction diameter [mm]	80
Backflow diameter (mm)	80
Outflow maximum (L/min)	900
Outflow maximum (m3/h)	54
Lifting height (m)	26
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Yes

### Engine specifications

Engine trademark	Honda
Engine type	GX 160
Distribution	O.H.V.
Start	Launcher
Fuel	Petrol (unlead)
Autonomy (h)	3.4
Consumption (L/h)	.9
Tank (L)	3.1
Oil Guard	Yes
HP 3600 tr/mn max.	4.8
Capacity (cm3)	163
Oil capacity (L)	.6

### Dimensions and weight

Length (cm)	50.5
Width (cm)	39.8
Height (cm)	46.6
Dry Weight (kgs)	29

### Packaging

Packaging type	Box
Length (cm)	51.5
Width (cm)	42
Height (cm)	48
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	157

## Delivered accessories



Inlet filter



Circlips



Screw-on connectors

## Options



RHO      **Cover**      Cover for SDMO generator sets and petrol or diesel driven pumps



R12      **Piping kit R12**      Piping kit for 3 water pumps made up of 5 m suction + 25 m lift.



R14      **Rapid connections kit R14**      Rapid connections kit for 3 water pumps.

