



TECHNIC 7500 TE AVR M

PORTABLE POWER

Generating Sets Range TECHNIC

PRODUCT ADVANTAGES

- Entire group guaranteed 3 years
- KOHLER air-cooled industrial engine
- Connection interface equipped with an hour meter and the MODYS control unit
- Electric starter with batteries without maintenance
- AVR : Automatic tension regulation

QUAD CLEAN AIR FILTER The Cyclonic Quad Clean air filters provide 4 levels of filtration which effectively filter out large particles and capture the finest particles. They ensure a continuous supply of clean air to the engine, fuel economies, increase the engine performance and extend its lifetime

AVR By regulating the voltage electronically by $\pm 2\%$, depending on the model, the AVR eliminates all risk of damage to boilers or certain kinds of electronic equipment.

Range TECHNIC

A long run time equipment that can withstand extreme conditions, for daily professional use.



This product meets the Qualigen charter, which aims to ensure a high level of quality and guarantee the safety of users. Qualigen commitment to safety and quality.

TECHNIC 7500 TE AVR M

GENERAL SPECIFICATIONS

Range	TECHNIC
Frequency (Hz)	50
Max power LTP (kW) *	6.50
Max power LTP (kVA)	8.10
Nominal voltage (V)	400
Number of Phase	Three phase
Fuel	Petrol
Tank (L)	18
75% cons. (l/h) *	2.60
75% Autonomy (h) *	6.90
Sound power level guaranteed LwA dB(A)	97
Acoustic pressure level @1m in dB(A)	83
Acoustic pressure level @7m in dB(A)	69

ENGINE SPECIFICATIONS

Engine model	KOHLER
Engine ref.	CH440E
Distribution	O.H.V.
Start	Electrical Starter
Oil Guard	Oui
Capacity (cm3)	429
Oil capacity (L)	1.10

ALTERNATOR SPECIFICATIONS

Technology	Without collar or brush
AVR Regulation	Yes
Indication of protection	IP 23
Insulation class	H

PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 400V 16A socket - circuit breaker + hour meter

DIMENSIONS AND WEIGHT

Length (cm)	81
Width (cm)	55.50
Height (cm)	59
Dry Weight (kgs)	102

PACKAGING

Packaging type	Box
Length (cm)	82
Width (cm)	56.50
Height (cm)	60
Weight (kg)	105
Pallet type	120/80
Number of box by pallet	6
Pallet height (cm)	193
weight of the packaged Pallet (kg)	640



TECHNIC 7500 TE AVR M - PORTABLE POWER - Generating Sets TECHNIC

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 12bis, rue de la Villeneuve - CS 92848 - 29228 BREST CEDEX 2 - France - Tel +33(0)2 98 41 41 41 - Fax +33 (0)2 98 41 63 07 - www.sdmo.com

3/23/2015

ACCESSORIES SUPPLIED



Funnel



Floor maintaining slot



Battery without maintenance



User and maintenance manual



Ergonomic handle grip

OPTIONS



RSTART

Wireless remote

Remote control in order to start or stop the generating set until a distance of 50 meters (needs the installation of a MODYS control panel)



VERS05
0

Automatic start panel

Switches over automatically if the mains fails, 40A or 100A 1P or if the mains fails, 25A or 40A 3P (needs the installation of a MODYS control panel). Includes the battery charger.



RKB1

Trolley kit

Trolley kit for the generating sets of 6kW or below



RKS2

Maintenance kit for
KOHLER engines

Maintenance kit for KOHLER CH395 and CH440 engines.



RH1

Protection cover

Cover for SDMO's generating sets, welding sets and water pumps



RPM

Set of male plugs

Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V



RPQ

Earth spike

For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm² cable.



RLIFT2

Lifting eye

Central lifting yoke